

P.2-101 <規格表>

T寸選択タイプ(並級)のD40・50のV選択に10と12を追加。

型式 Type	D	V 選択	T 選択	Y基準単価						
				WSSB	WSSM	WSSS	WSSBH	WSSMH	WSSSH	
WSSB WSSM WSSS WSSBH WSSMH WSSSH	4	2	1 2	70	95	110	85	110	140	
	5	2 3	1 2							
	6	2 3 4	1 2							
		3 4	1.5 3 5 6	90 100						
	8	2 3 4 5 6	1 2 3 5	70 95						
		3 4 5 6	1.5 4 6 8	90 100	120	—	—	—		
	10	2 3 4 5 6 8	1 2 3 5	95 115	125	110	125	170		
		4 5 6 8	1.5 2.5 4 6 8	100 120	140	—	—	—		
	12	3 4 5 6 8 10	1 2 3 5	95	115	125	110	125	170	
		5 6 8 10	1.5 2.5	100		140	—	—	—	
		6 8	4 6 8	100	115	140	—	—	—	
	13	4 5 6 8 10	1 2 3 5	110	130	140	125	140	180	
		6 8	1.5 2.5			150	—	—	—	
	14	4 5 6 8 10	1 2 3 5	120		140	140	125	140	180
		6 8 10	1.5		160		—	—	—	
	15	4 5 6 8 10 12	1 2 3 5	125	150		150	140	155	210
		6 8 10 12	1.5	130		170	—	—	—	
	16	4 5 6 8 10 12	1 2 3 5	125	140	140	150	140	155	210
		6 8 10 12	1.5	140		160	180	—	—	—
		10 12	4	140		160	180	—	—	—
	20	4 5 6 8 10 12 15 16	1	140	150	170	—	—	—	
		6 10 15	2 3 5			150	170	190	—	—
		6 8 10 12 15 16 20	1.5 2.5 4 6 8	150		170	190	—	—	—
	25	6 8 10 12 15 16 20	2 3 5	140	190	210	175	200	250	
	30	8 10 12 15 16 20 25	2 3 5			220	240	175	255	280
	35	10 12 15 16 20 25	3 5 10	220		240	175	255	280	
40	10 12 15 16 20 25 30	3 5 10	160	270	300	215	310	360		
50	10 12 15 16 20 25 30	3 5 10	210	320	350	260	370	410		
60	15 16 20 25 30	3 5 10	250	380	400	300	440	490		

<訂正用>

10 12
10 12