

P.2-1081<規格表>

D250サイズのみb=5、t=2.3に変更。

型式		H	A	D ₁	L	S	M		B	G		P	H8穴+タップ		H8穴+キー溝+タップ		角穴	スリット					六角穴付ボルト			参考質量 (g)																							
Type	D						スチール	アルミ		固定	回転		d	M ₁ (並目)	d ₁	b		t	W選択	d ₂	S ₁	X	Y	R (半径)	d _s	M ₁ (並目)	AHLND 参考締付トルク (N・m)	AHLNF 参考締付トルク (N・m)	スチール	アルミ																			
穴無し	穴・グリップ無し	80	36	14	24	24	5	13	38.5	49	28	10	10	3	1.4	10	*10	12	9	8	8.5	4.5	4	3	3	380	160																						
AHLN	AHLN-R	100	39	16	30	15					8						16											48.5	55	37	5	12	4	1.8	12	10	12	10	9	9	9.5	5.5	5	5	600	250			
AHLNA	H8穴+タップ																																			*12											13	8	5
AHLNK	AHLNM	125	40	17	33	28	6	16	48.5	55	46.5	12	5	12	4	1.8	12	*12	13	8	9.5	5.5	5	6	6	900	345																						
AHLNAK	AHLNKM	140	44	18	35	30	6	16	48.5	55	53.5	15	15	5	2.3	14	*15	—	—	—	—	—	—	—	—	—	1100	425																					
AHLNK	H8穴+キー溝+タップ																160	46	18.5	37	32	8	20	62.5	70.7	62.5	16	6	16	5	2.3	14	16	15	10.5	12.5	6.5	6	10	—	1400	560							
AHLNKCK																	160	46	18.5	37	32	8	20	62.5	70.7	62.5	16	6	16	5	2.3	14	20	15	10.5	12.5	6.5	6	10	—	1400	560							
スリット	角穴	200	59.5	24	43	41	10	25	77.5	87.3	81	16	6	16	5	2.3	17	16	14	16.5	11	12.5	6.5	6	11	—	2800	1140																					
AHLNF	AHLNW	250	65.5	27	48	44												—											—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
AHLND	AHLNKW	250	65.5	27	48	44												—											—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—

<訂正用>

b	t
3	1.4
4	1.8
5	2.3
5	2.3
5	2.3