

赤枠内の表記を一部変更

Catalog No.		ラバー位置	L寸指定	A	B	C	W	D	t	最小曲半径mm			対応可能板厚 (T寸の許容範囲)	¥単価/1m			
Type	T									曲げ方向①	曲げ方向②	曲げ方向③					
TRSAT	1.6	X (実線部) Y (点線部)	1~75 (1m単位)	6.0	14.5	15.5	1.6	9.5	1.3	30	30	20	1.2~1.8	1,190			
	3.2			7.6	14.0	17.1	3.2					30	2.8~3.6				
	4.8			9.2	13.6	18.7	4.8						4.2~5.4				
	6.4			10.8	12.7	20.3	6.4						5.5~7.0				
TRSBT	1.6			X (実線部)	1~75 (1m単位)	6.0	14.5	17.1	1.6	11.1	1.5	30	30	50	1.2~1.8	1,260	
	3.2					7.6	14.0	18.7	3.2					50	2.8~3.6		
	4.8					9.2	13.6	20.3	4.8						4.2~5.4		
	6.4					10.8	12.7	21.9	6.4						5.5~7.0		
TRSCT	1.6			Y (点線部)		1~75 (1m単位)	6.0	14.5	21.9	1.6	15.9	2.0	60	60	70	1.2~1.8	1,340
	3.2						7.6	14.0	23.5	3.2					70	2.8~3.6	
	4.8						9.2	13.6	25.1	4.8						4.2~5.4	
	6.4						10.8	12.7	26.7	6.4						5.5~7.0	
TRSDT	1.6	X(実線部)	1~75 (1m単位)	5.4			10.0	12.4	1.6	7.0	1.3	30	30	—	1.2~1.8	1,260	
TRSASB	3.2	—		9.6			13.2	24.0	4.6	10.0	1.2	95	170	50	1.0~3.2	2,740	
TRSASG				—			9.6	13.2	20.0	4.6	10.4	1.2	50	50	—	1.0~3.2	2,740
TRSBSB																	
TRBSBG																	
TRSCSB	3.2	—		9.6	12.0		18.5	4.6	6.5	1.2	50	90	35	1.0~3.2	2,670		
TRSCSG																	

<訂正用>

24.0

20.0

18.5