

キリ穴&ノック穴タイプのa寸条件式訂正

■キリ穴&ノック穴タイプ

型式		イケール本体				キリ穴								ノック穴				
Type	H	A 指定5mm単位	W 選択	T	T ₁	d		B			X	F	Y	G	DH7		a	h
						W=60	W=75・100	W=60	W=75	W=100					W=60	W=75		
IKCK BIKCK MIKCK AIKCK	100	50	75 100	15	14	—	11	—	50	70	35	—	45	40	—	10	—	65
		80~100										X+(F/2)						
	150	65~75	60 75 100	15	14	9	11	40	50	70	35	—	75	60	6	10	A-15	105
		80~100	75 100			—		A-50				—			X+(F/2)			
	200	65~75	60 75	15	14	9	11	40	50	—	35	—	110	70	6	10	A-15	145
		85~120	75 100			—		70		40		A-50			—		X+(F/2)	
	250	85~120	75 100	18	15	—	11	—	50	70	40	A-55	140	90	—	10	X+(F/2)	185
	300	90~150																190
350	90~150	18		15	—	11	—	50	70	40	A-60	230	100	—	10	280		
400	90~150															260		120

①材質アルミAC7Aでは、W60は指定不可。

<訂正用>

X+(F/2)
A-15
X+(F/2)
A-15
X+(F/2)
X+(F/2)