

P.937 (規格表)

ツバなしタイプDh710・10TのQ寸訂正

型式		P		Q	F・B	L	A	E(A形状)	ℓ	L1	ℓ1	d	適用 止めねじ	¥単価 1~4コ				
Type	先端形状	Dh7	指定0.1mm単位	指定0.1mm単位	指定1mm単位	選択	選択	指定1mm単位						WLNNA	WLNTA	TWLNNA	TWLNTA	
WLNNA WLNTA TWLNNA TWLNTA	指定無 (角度30° テーパー)	6	$-\overset{0}{0.012}$	8.0~12.0	7.0~11.0	3~45	5 8 10	30	1~10	6	8	8	4	M5	1,090	1,090	2,050	2,050
		8	0	10.0~16.0	9.0~15.0		5 8 10 12 15			10			5		1,400	1,400	2,090	2,090
	10	-0.015	12.0~20.0	10.0~19.0	5 8 10 12 15		12			10	7	M6	1,650	1,650	2,110	2,110		
	10T				5 8 10 12 15		18				5		1,650	1,650	2,110	2,110		
	A (テーパー) B (角度選択 テーパー)	12	0	14.0~25.0	13.0~24.0		8 10 12 15 18	90		15	10	9	M8	2,110	2,110	2,550	2,550	
		16	-0.018	18.0~32.0	17.0~31.0		10 12 15 18 20	120		18		12		13	2,550	2,550	2,880	2,880
		20	$-\overset{0}{0.021}$	22.0~35.0	21.0~34.0		12 15 18 20	22		17		2,920		2,920	3,680	3,680		
							12 15 18 20	2,920		2,920		3,680		3,680				

①P-1≥Q ②B+2+F≤50 ③従来のRC追加工(角度変更)は先端B形状で代替できます。

<訂正用> [10.0~19.0]