

P.1918 < 規格表 >

抜差し蝶番 適用ボルトをCBM→CBSに変更

Catalog No.		*許容荷重		質量 (g)	W	J	S	D	d	h	適用ボルト・ナット				¥単価	
Type	No.	kg	N								ボルト	個数	ナット	個数	1~9コ	10~
HHPNLK HHPNRK	5-25	10	98	86	41	7.5	26	9.5	5.5	4.1	CBS5-8	4	HNTT5-5	4	405	380
	6			103	55	12	31				CBS6-12		HNTT6-6		465	440
	8	15	147	120	73	16	41	11	6.5	4.4	CBS6-15		HNTT8-6		515	490
	8-45			130	83	18.5	46				575		550			

Catalog No.		*許容荷重		質量 (g)	W	J ₁	F ₁	D	d	h	J ₂	F ₂	適用ボルト・ナット				¥単価			
Type	No.	kg	N										ボルト	個数	ナット	個数	1~9コ	10~		
HHPNDLK HHPNDRK	6-5	10	98	95	48	12	15.5	9.5	5.5	4.1	7.5	13	CBS5-8・CBS6-12	各2個	HNTT5-5・HNTT6-6	各2個	465	440		
	8-5			103	57	16	20.5				7.5	13			CBS5-8・CBS6-15		HNTT5-5・HNTT8-6	515	490	
	845-5	15	147	108	62	18.5	23	11	6.5	4.4	7.5	13	CBS5-8・CBS6-15	各2個	HNTT5-5・HNTT8-6	各2個	575	550		
	8-6			111	64	16	20.5				12	15.5					CBS6-12・CBS6-15	HNTT6-6・HNTT8-6	515	490
	845-6			116	69	18.5	23				12	15.5							575	550