

COLLARS -STANDARD TYPE-  
**金属カラー**  
 -並級 L寸選択タイプ-

類似寸法は加工部品Cナビ <http://cp.misumi.jp/10-013/>

RoHS

| Type   | 並級     | 材質 | 表面処理       |
|--------|--------|----|------------|
| KNCLB  | S45C   | —  | 四三酸化鉄皮膜    |
| KNCLM  |        |    | 無電解ニッケルメッキ |
| KNCLSS | SUS304 | —  | —          |

※ D=16以下 C0.1~0.2  
D=20以上 C0.5以下

**並級**

| 型式<br>Type               | V  | D 選択 |    |    |    |    |    |    |    |    |    | L 選択 |    |    |    |    |    |    |
|--------------------------|----|------|----|----|----|----|----|----|----|----|----|------|----|----|----|----|----|----|
|                          |    | 3    | 5  | 6  | 8  | 10 | 12 | 13 | 14 | 15 | 16 | 20   | 10 | 12 | 15 | 20 | 25 | 30 |
| KNCLB<br>KNCLM<br>KNCLSS | 3  | 5    | 6  | 8  | 10 | 12 |    |    |    |    |    |      |    |    |    |    |    |    |
|                          | 4  | 6    | 8  | 10 | 12 | 13 | 14 | 15 | 16 | 20 |    |      |    |    |    |    |    |    |
|                          | 5  | 8    | 10 | 12 | 13 | 14 | 15 | 16 | 20 |    |    |      |    |    |    |    |    |    |
|                          | 6  | 8    | 10 | 12 | 13 | 14 | 15 | 16 | 20 | 25 |    |      |    |    |    |    |    |    |
|                          | 8  | 10   | 12 | 13 | 14 | 15 | 16 | 20 | 25 | 30 |    |      |    |    |    |    |    |    |
|                          | 10 | 12   | 13 | 14 | 15 | 16 | 20 | 25 | 30 |    |    |      |    |    |    |    |    |    |
|                          | 12 |      |    |    | 15 | 16 | 20 | 25 | 30 |    |    |      |    |    |    |    |    |    |
|                          | 15 |      |    |    |    | 20 | 25 | 30 |    |    |    |      |    |    |    |    |    |    |
|                          | 16 |      |    |    |    | 20 | 25 | 30 |    |    |    |      |    |    |    |    |    |    |
|                          | 20 |      |    |    |    |    | 25 | 30 |    |    |    |      |    |    |    |    |    |    |
| 25                       |    |      |    |    |    |    | 30 |    |    |    |    |      |    |    |    |    |    |    |

Order 注文例: 型式 **KNCLB3** - **D 5** - **L 10**

Price 価格

数量スライド価格 (1円未満切り捨て) P89

| 数量   | 1~9 | 10~19 | 20~49 | 50~99 |
|------|-----|-------|-------|-------|
| 値引率  | —   | 5%    | 10%   | 15%   |
| 基準単価 | —   | —     | —     | —     |

表示数量超えはお見積り

Delivery 出荷日: 在庫品 翌日出荷 P89

ご希望によりPM5:00迄、当日出荷受付致します。

| 型式<br>Type | D   | ¥基準単価 |     |     |     |     |     |     |  |
|------------|-----|-------|-----|-----|-----|-----|-----|-----|--|
|            |     | L10   | L12 | L15 | L20 | L25 | L30 | L35 |  |
| KNCLB      | 5   | 160   | 160 | 170 | 180 | 190 | 200 | 200 |  |
|            | 6   | 160   | 160 | 170 | 180 | 190 | 200 | 210 |  |
|            | 8   | 160   | 170 | 180 | 200 | 200 | 200 | 210 |  |
|            | 10  | 170   | 180 | 190 | 200 | 200 | 200 | 210 |  |
|            | 12  | 180   | 190 | 200 | 220 | 220 | 220 | 230 |  |
|            | 13  | 200   | 210 | 220 | 230 | 230 | 230 | 240 |  |
|            | 14  | 220   | 220 | 230 | 240 | 240 | 240 | 250 |  |
|            | 15  | 230   | 230 | 250 | 250 | 250 | 250 | 260 |  |
|            | 16  | 230   | 230 | 250 | 250 | 250 | 260 | 260 |  |
|            | 20  | 240   | 240 | 250 | 260 | 260 | 270 | 280 |  |
| 25         | 290 | 320   | 340 | 360 | 360 | 370 | 380 |     |  |
| 30         | 320 | 330   | 340 | 360 | 360 | 370 | 380 |     |  |
| KNCLM      | 5   | 170   | 170 | 180 | 200 | 200 | 200 | 210 |  |
|            | 6   | 170   | 170 | 190 | 200 | 210 | 210 | 220 |  |
|            | 8   | 170   | 190 | 210 | 230 | 230 | 230 | 230 |  |
|            | 10  | 180   | 200 | 220 | 230 | 230 | 230 | 230 |  |
|            | 12  | 200   | 220 | 240 | 250 | 250 | 250 | 250 |  |
|            | 13  | 220   | 240 | 250 | 260 | 260 | 260 | 260 |  |
|            | 14  | 240   | 240 | 250 | 260 | 260 | 260 | 260 |  |
|            | 15  | 260   | 260 | 280 | 290 | 290 | 290 | 290 |  |
|            | 16  | 270   | 270 | 300 | 300 | 300 | 300 | 300 |  |
|            | 20  | 280   | 280 | 300 | 310 | 310 | 310 | 310 |  |
| 25         | 340 | 380   | 400 | 430 | 430 | 430 | 430 |     |  |
| 30         | 380 | 390   | 400 | 430 | 430 | 430 | 430 |     |  |
| KNCLSS     | 5   | 210   | 220 | 240 | 250 | 290 | 300 | 310 |  |
|            | 6   | 210   | 220 | 240 | 250 | 290 | 300 | 310 |  |
|            | 8   | 220   | 250 | 270 | 290 | 290 | 300 | 310 |  |
|            | 10  | 250   | 260 | 280 | 300 | 330 | 340 | 350 |  |
|            | 12  | 260   | 280 | 300 | 330 | 360 | 380 | 390 |  |
|            | 13  | 270   | 290 | 310 | 340 | 360 | 380 | 390 |  |
|            | 14  | 300   | 310 | 320 | 340 | 360 | 380 | 390 |  |
|            | 15  | 330   | 340 | 370 | 380 | 380 | 390 | 400 |  |
|            | 16  | 330   | 340 | 370 | 380 | 380 | 390 | 400 |  |
|            | 20  | 340   | 350 | 380 | 390 | 450 | 480 | 490 |  |
| 25         | 420 | 460   | 490 | 520 | 520 | 520 | 550 |     |  |
| 30         | 420 | 460   | 490 | 520 | 590 | 630 | 690 |     |  |

※価格は外径(D)基準です。

COLLARS -STANDARD TYPE-  
**金属カラー**  
 -並級・精密級 L寸指定タイプ-

類似寸法は加工部品Cナビ <http://cp.misumi.jp/10-013/>

RoHS

| Type  | L寸指定タイプ | 並級    | 精密級 | 材質     | 表面処理                               |
|-------|---------|-------|-----|--------|------------------------------------|
| NCLC  | ACSC    | S45C  | —   | —      | —                                  |
| NCLB  | ABSC    |       |     |        |                                    |
| NCLM  | AMSC    |       |     |        |                                    |
| NCLA  | AASC    |       |     |        |                                    |
| NCLSS | SASC    | A2017 | —   | SUS304 | 四三酸化鉄皮膜<br>無電解ニッケルメッキ<br>アルマイト(白色) |

※ D=16以下 C0.1~0.2  
D=20以上 C0.5以下

焼入品はP119

**並級・精密級**

| 型式<br>Type                                    | V   | D 選択                             | L 指定<br>0.1mm単位           | ¥基準単価      |       |       |       |       |       |       |       |       |       |     |
|---|---|----------------------------------|---------------------------|------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-----|
|   |   |                                  |                           | 並級         |       |       |       |       | 精密級   |       |       |       |       |     |
|   |   |                                  |                           | NCLC       | NCLB  | NCLM  | NCLA  | NCLSS | ACSC  | ABSC  | AMSC  | AASC  | SASC  |     |
| —並級—<br>NCLC<br>NCLB<br>NCLM<br>NCLA<br>NCLSS | 2   | 4 5 6 8 10                       | 10.0~16.0                 | 150        | 160   | 180   | 190   | 250   | 240   | 260   | 270   | 290   | 370   |     |
|   | 3   | 5 6 8 10 12                      | 10.0~25.0                 | 150        | 160   | 180   | 190   | 250   | 240   | 260   | 270   | 290   | 370   |     |
|   | 4 5 6   | (6) 8 10 12 13 14 15 16          | ①(6)→V4に適用                | 10.0~25.0  | 150   | 160   | 180   | 190   | 390   | 240   | 260   | 270   | 290   | 490 |
|   |   |                                  |                           | 25.1~50.0  | 160   | 170   | 190   | 200   | 430   | 260   | 280   | 290   | 310   | 530 |
|   |   |                                  |                           | 25.1~50.0  | 160   | 170   | 190   | 200   | 450   | 260   | 280   | 300   | 320   | 560 |
|   | —精密級—<br>ACSC<br>ABSC<br>AMSC<br>AASC<br>SASC | 8 10 12                          | (10) (12) (13) (14) 15 16 | 10.0~25.0  | 200   | 210   | 220   | 250   | 400   | 300   | 310   | 320   | 350   | 500 |
|   |   |                                  |                           | 25.1~50.0  | 210   | 250   | 240   | 290   | 450   | 310   | 350   | 340   | 390   | 550 |
|   |   |                                  |                           | 50.1~75.0  | 380   | 390   | 400   | 400   | 500   | 480   | 490   | 500   | 500   | 610 |
|   |   |                                  |                           | 75.1~100.0 | 490   | 500   | 510   | 510   | 630   | 610   | 620   | 630   | 650   | 770 |
|   |   |                                  |                           | 10.0~25.0  | 220   | 230   | 260   | 270   | 500   | 330   | 350   | 360   | 390   | 620 |
| 25.1~50.0                                     |   |                                  |                           | 360        | 370   | 380   | 380   | 550   | 480   | 490   | 500   | 510   | 670   |     |
| 50.1~75.0                                     |   |                                  |                           | 510        | 520   | 530   | 530   | 780   | 630   | 650   | 650   | 660   | 910   |     |
| 75.1~100.0                                    |   |                                  |                           | 660        | 670   | 680   | 680   | 970   | 800   | 810   | 820   | 820   | 1,110 |     |
| 10.0~25.0                                     |   |                                  |                           | 350        | 370   | 380   | 380   | 540   | 520   | 550   | 570   | 560   | 700   |     |
| 25.1~50.0                                     |   |                                  |                           | 640        | 660   | 670   | 670   | 1,000 | 810   | 840   | 860   | 850   | 1,150 |     |
| 10 12   | 20 25   | ①(10)→V8に適用 ②(12 13 14)→V8・10に適用 | 10.0~25.0                 | 930        | 940   | 960   | 960   | 1,460 | 1,110 | 1,140 | 1,170 | 1,160 | 1,630 |     |
|   |   |                                  | 25.1~50.0                 | 1,120      | 1,200 | 1,220 | 1,250 | 1,910 | 1,300 | 1,400 | 1,430 | 1,450 | 2,080 |     |
|   |   |                                  | 50.1~75.0                 | 610        | 700   | 750   | 780   | 1,360 | 780   | 870   | 920   | 960   | 1,540 |     |
|   |   |                                  | 75.1~100.0                | 820        | 910   | 1,050 | 1,150 | 2,380 | 990   | 1,080 | 1,220 | 1,330 | 2,560 |     |
|   |   |                                  | 10.0~25.0                 | 1,190      | 1,340 | 1,400 | 1,500 | 3,400 | 1,370 | 1,530 | 1,580 | 1,690 | 3,590 |     |
|   |   |                                  | 25.1~50.0                 | 1,350      | 1,530 | 1,500 | 1,750 | 4,760 | 1,530 | 1,720 | 1,680 | 1,940 | 4,950 |     |
|   |   |                                  | 50.1~75.0                 | 230        | 250   | 280   | 300   | 530   | 370   | 400   | 420   | 450   | 680   |     |
|   |   |                                  | 75.1~100.0                | 420        | 430   | 440   | 450   | 610   | 560   | 580   | 590   | 600   | 760   |     |
|   |   |                                  | 10.0~25.0                 | 540        | 540   | 560   | 600   | 860   | 680   | 690   | 710   | 750   | 1,010 |     |
|   |   |                                  | 25.1~50.0                 | 750        | 770   | 780   | 790   | 1,150 | 890   | 930   | 940   | 950   | 1,300 |     |
| 15 16 20                                      | 30 35   | ①(20)→V15・16に適用                  | 10.0~25.0                 | 410        | 430   | 450   | 450   | 630   | 570   | 600   | 600   | 620   | 800   |     |
|   |   |                                  | 25.1~50.0                 | 740        | 760   | 780   | 780   | 1,160 | 920   | 930   | 940   | 950   | 1,340 |     |
|   |   |                                  | 50.1~75.0                 | 1,080      | 1,100 | 1,120 | 1,120 | 1,700 | 1,260 | 1,280 | 1,300 | 1,300 | 1,880 |     |
|   |   |                                  | 75.1~100.0                | 1,140      | 1,220 | 1,240 | 1,280 | 1,950 | 1,330 | 1,430 | 1,460 | 1,480 | 2,120 |     |
|   |   |                                  | 10.0~25.0                 | 640        | 680   | 780   | 810   | 1,390 | 810   | 850   | 950   | 990   | 1,570 |     |
|   |   |                                  | 25.1~50.0                 | 850        | 940   | 1,080 | 1,180 | 2,410 | 1,020 | 1,110 | 1,250 | 1,360 | 2,590 |     |
|   |   |                                  | 50.1~75.0                 | 1,210      | 1,370 | 1,430 | 1,530 | 3,430 | 1,390 | 1,560 | 1,610 | 1,720 | 3,620 |     |
|   |   |                                  | 75.1~100.0                | 1,380      | 1,560 | 1,530 | 1,700 | 4,790 | 1,560 | 1,750 | 1,710 | 1,890 | 4,980 |     |
|   |   |                                  | 10.0~25.0                 | 440        | 460   | 480   | 480   | 660   | 600   | 630   | 630   | 650   | 830   |     |
|   |   |                                  | 25.1~50.0                 | 770        | 790   | 810   | 810   | 1,190 | 950   | 960   | 970   | 980   | 1,370 |     |
| 50.1~75.0                                     | 1,110   | 1,130                            | 1,150                     | 1,150      | 1,730 | 1,290 | 1,310 | 1,330 | 1,310 | 1,910 |       |       |       |     |
| 75.1~100.0                                    | 1,160   | 1,240                            | 1,260                     | 1,310      | 1,990 | 1,360 | 1,460 | 1,490 | 1,510 | 2,160 |       |       |       |     |
| 25 30   | 40 50 60                                      |                                  | 10.0~25.0                 | 670        | 710   | 810   | 840   | 1,420 | 840   | 880   | 980   | 1,020 | 1,600 |     |
|   |   |                                  | 25.1~50.0                 | 880        | 970   | 1,110 | 1,210 | 2,440 | 1,050 | 1,140 | 1,280 | 1,390 | 2,620 |     |
|   |   |                                  | 50.1~75.0                 | 1,240      | 1,400 | 1,460 | 1,560 | 3,460 | 1,420 | 1,590 | 1,640 | 1,750 | 3,650 |     |
|   |   |                                  | 75.1~100.0                | 1,410      | 1,590 | 1,560 | 1,700 | 4,820 | 1,590 | 1,740 | 1,740 | 1,890 | 5,010 |     |

Order 注文例: 型式 **NCLB3** - **D 5** - **L 10.5**

Price 価格

数量スライド価格 (1円未満切り捨て) P89

| 数量   | 1~9 | 10~19 | 20~49 | 50~99 | 100~200 |
|------|-----|-------|-------|-------|---------|
| 値引率  | —   | 5%    | 10%   | 15%   | 18%     |
| 基準単価 | —   | —     | —     | —     | —       |

出荷日: 通常

表示数量超えはWOSにてご確認ください。

材質 S45C・SUS304

3 日目発送

ストーク A 200円/1本 P90

同一サイズ3本以上は一律540円

材質 A2017

5 日目発送

ストーク B 200円/1本 P90

大口出荷 +4 日目出荷 数量 100~200

同一サイズ3本以上は一律540円

ストーク対応なし

34  
カラー・シム  
ワッシャー