

■ホース用おねじニッブル

Type	材質
HOSN	黄銅
HOSNS	SUS304

RoHS

型式 Type	No.	適応ホース 呼び内径	T R (PT)	D	HOSN					HOSNS					HOSN		HOSNS	
					d	H	L	L1	d	H	L	L1	1~19コ	20~49コ	1~9コ	10~29コ		
					¥基準単価	¥スライド単価	¥基準単価	¥スライド単価	¥基準単価	¥スライド単価	¥基準単価	¥スライド単価						
HOSN (黄銅)	61	6	1/8	7	4	12	34	20	4	12	36	20	130	80	500	470		
	62	6	1/4	7	4	14	41	26	4	14	42	24	150	90	600	510		
	63	6	3/8	7	4	17	46	29	4	17	44	25	180	130	650	600		
	64	6	1/2	7	3.5	22	50	29	4	22	49	27	240	210	1,070	790		
	628	6	1/4	8	4.5	14	41	26	5	14	42	24	360	270	760	640		
	629	6	1/4	9	5	14	41	26	5	14	42	24	360	270	760	640		
	91	9	1/8	10.5	6	12	34	20	6	12	36	20	140	90	600	510		
	92	9	1/4	10.5	7	14	41	26	6	14	42	24	150	90	500	470		
	93	9	3/8	10.5	7	17	46	29	6	17	44	25	170	120	520	490		
HOSNS (SUS304)	94	9	1/2	10.5	6	22	50	29	7	22	49	27	230	190	900	790		
	12412	12	1/2	12	7.5	22	50	29	8	22	49	27	450	330	950	800		
	122	12	1/4	14	9	14	41	26	8	17	42	24	170	110	600	570		
	123	12	3/8	14	10	17	46	29	9	17	44	25	180	130	600	570		
	124	12	1/2	14	10	22	50	29	11	22	49	27	220	180	750	710		
	153	15	3/8	16	11	17	46	29	11	17	44	25	460	390	820	690		
	154	15	1/2	16	11	22	50	29	12	22	49	27	500	420	940	790		
	19619	19	3/4	19	13	27	60	36	14	27	59	33	750	630	1,430	1,210		
	194	19	1/2	20.5	14	22	50	29	15	22	49	27	270	220	900	790		
258	25	1	27	20.5	35	74	42	22	35	70	40	850	750	1,510	1,380			
3812	38	1 1/2	40	30	51	100	61	31	52	90	53	2,060	1,900	2,270	2,110			
5016	50	2	52	40	63	132	86	43	63	100	60	3,550	3,310	2,980	2,780			

■ホース用めねじニッブル

Type	材質
HOSFNS	SUS304

RoHS

型式 Type	No.	適応ホース 呼び内径	T Rc (PT)	D	d	H	L	L1	¥基準単価		¥スライド単価	
									1~9コ	10~29コ	1~9コ	10~29コ
									HOSFNS (SUS304)	92	6	1/4
93	9	3/8	10.5	7.0	22	49	28	1,130		900		
123	12	1/2	14	10.0	24	54	29	1,380		1,100		
124	12	1/2	14	10.0	24	54	29	1,380	1,100			

■ホース用タケノコジョイント

Type	材質
HOSJJS	SUS304

RoHS

型式 Type	No.	適応ホース 呼び内径	D	d	L	¥基準単価		¥スライド単価	
						1~9コ	10~29コ	1~9コ	10~29コ
						HOSJJS (SUS304)	6	6	7.0
9	9	10.5	8.0	70	1,270		1,200		
12	12	14.0	10.0	75	1,720		1,630		
19	19	20.5	16.0	90	3,470		3,290		

■ホース用ジョイントニッブル

Type	材質
HOSJN	黄銅
HOSJNS	SUS304

RoHS

型式 Type	No.	適応ホース 呼び内径	T R (PT)	D	T1 G (PF)	d	H	H1	(L)	L1	HOSJN		HOSJNS	
											1~9コ	10~29コ	1~9コ	10~29コ
											HOSJN (黄銅)	61	6	1/8
62	6	1/4	7.0	1/4	4.0	14	16	59	26	400		280	—	—
63	6	3/8	7.0	1/4	4.0	17	16	60	26	440		300	—	—
628	6	1/4	8	1/4	4.5	14	16	59	26	520		390	—	—
HOSJNS (SUS304)	629	6	1/4	9	1/4	5	14	16	59	26	520	390	—	—
	92	9	1/4	10.5	3/8	7.0	17	19	57	27	520	360	—	—
	93	9	3/8	10.5	3/8	7.0	17	19	60	27(25)	520	360	2,660	2,390
	94	9	1/2	10.5	3/8	7.0	22	19	63	27	680	470	—	—
	123	12	1/2	12	1/2	10.0	22	24	71	31	680	470	—	—
	124	12	1/2	14	1/2	10.0(10.5)	22	24	73(69)	31(27)	730	510	3,370	2,533
	126	12	3/4	14	1/2	10.0	28	24	77	31	1,260	880	—	—
	153	15	3/8	16	1/2	11.5	22	24	71	31	760	570	—	—
	154	15	1/2	16	1/2	11.5	22	24	73	31	760	570	—	—
	194	19	1/2	19	3/4	15.0	28	30	78	35	1,300	910	—	—
	196	19	3/4	20.5	3/4	15.0	28(29)	30	82(80)	35(33)	1,350	940	4,800	3,600

仕様

使用流体	水・空気・油
使用温度範囲	-50~150°C (但し凍結なきこと)
最高使用圧力	3.45MPa

組立手順 (HOSJE・HOSJH・HOSJT)

- 1) ホースナットにホース口をはめ込んでください。
- 2) ホース口R面(シート面)を本体内面にあててください。
- 3) ホースナットを手締めしてください。
- 4) スパナ及びモンキーレンチ等できっちりと締めこんでください。

■両口ホースジョイント

Type	材質
HOSSH	黄銅

RoHS

型式 Type	No.	適応ホース 呼び内径	D	d	B1	B2	G (PF)	La	L	¥基準単価		¥スライド単価	
										1~4コ	5~9コ	1~4コ	5~9コ
										HOSSH (黄銅)	61	6	7
628	6	8	4.5	14	16	1/4	26	89	520		500		
629	6	9	5	14	16	1/4	26	89	520		500		
92	9	10.5	7	17	19	3/8	27	91	560		540		
123	12	14	10	22	24	1/2	31	112	810		770		
153	15	16	11.5	22	24	1/2	31	112	810		770		
196	19	20.5	15	27	30	3/4	35	120	1,220	1,160			

■ホース用タケノコジョイント

Type	材質
HOSHS	黄銅

RoHS

型式 Type	No.	適応ホース 呼び内径	D	d	A	¥基準単価		¥スライド単価	
						1~4コ	5~9コ	1~4コ	5~9コ
						HOSHS (黄銅)	628	6	8
629	6	9	5	34	310		300		
92	9	10.5	7	36	330		320		
123	12	14	10	42	360		350		
153	15	16	11.5	42	360		350		
196	19	20.5	15	46	470	450			

■ホース用袋ナット

Type	材質
HOSHJN	黄銅

RoHS

型式 Type	No.	本体 適用No.					G (PF)	D	B	A	¥基準単価		¥スライド単価	
		2	3	4	6	628					629	1~4コ	5~9コ	
		HOSHJN (黄銅)	2	62	63	628					629	1/4	9.5	16
3	92		93	94	3/8	11	19	14	340	330				
4	123		124	126	153	154	1/2	16.5	24	380	370			
6	194		196	3/4	21.5	30	17.5	500	480					

■ホース用エルボニッブル

Type	材質
HOSJE	黄銅

RoHS

型式 Type	No.	適応ホース 呼び内径	T R (PT)	F G (PF)	D	(L1)	(L2)	¥基準単価		¥スライド単価	
								1~9コ	10~29コ	1~9コ	10~29コ
								HOSJE (黄銅)	61	6	1/8
82	8	1/4	1/4	8	48.5	25	1,000		800		
93	9	3/8	3/8	10.0	56	28	1,540		1,230		
124	12	1/2	1/2	14.0	72	34	1,850		1,480		

■ホース用45°エルボニッブル

Type	材質
HOSJH	黄銅

RoHS

型式 Type	No.	適応ホース 呼び内径	T R (PT)	F G (PF)	D	(L1)	(L2)	¥基準単価		¥スライド単価	
								1~9コ	10~29コ	1~9コ	10~29コ
								HOSJH (黄銅)	61	6	1/8
82	8	1/4	1/4	8	48.5	25	1,300		970		
93	9	3/8	3/8	10.0	56	28	1,660		1,240		
124	12	1/2	1/2	14.0	72	34	2,370		1,770		

■ホース用フランチャーター

Type	材質
HOSJT	黄銅

RoHS

型式 Type	No.	適応ホース 呼び内径	T R (PT)	F G (PF)	D	(L1)	(L)	¥基準単価		¥スライド単価	
								1~9コ	10~29コ	1~9コ	10~29コ
								HOSJT (黄銅)	61	6	1/8