

六角穴付ボルト

—三価クロメート—

CADデータフォルダ名: 35_Screws

RoHS **CBE**

M 材質 SCM435
S 表面処理 三価クロメート
H 硬度 HRC32~39
 ※強度区分 10.9

M×P	A	E	B
2×0.4	3.8	2	1.5
2.6×0.45	4.5	2.6	2
3×0.5	5.5	3	2.5
4×0.7	7	4	3
5×0.8	8.5	5	4
6×1.0	10	6	5
8×1.25	13	8	6
10×1.5	16	10	8
12×1.75	18	12	10

※強度区分とは、ネジの引張強さです。

(例) 10.9
 降伏点または耐力の最小値が引張強さの90%であることを示します。
 引張強さの最小値が1040N/mm²であることを示します。

参考: 六角穴付ボルトに対するザグリ及びボルト穴の寸法 **P1777**

型式	ℓ	¥基準単価				¥スライド単価					
		Type M-L	1~9本	10~19本	20~49本	50本以上	Type M-L	1~9本	10~19本	20~49本	50本以上
CBE 2-5	全ねじ	5	120	72	48	30					
		6	120	72	48	30					
		8	120	72	48	30					
		10	120	72	48	30					
CBE 2.6-5	全ねじ	5	110	61	44	30					
		6	110	61	44	30					
		8	120	66	48	30					
		10	120	66	48	30					
CBE 3-4	全ねじ	4	79	55	32	25					
		5	69	31	28	22					
		6	69	31	28	19					
		8	69	31	28	19					
		10	74	33	30	22					
		12	74	33	30	22					
		15	74	33	30	22					
		18	74	33	30	22					
		20	74	33	30	22					
		25	77	35	31	24					
		30	82	37	33	28					
		35	82	45	33	28					
CBE 4-5	全ねじ	5	84	46	34	25					
		6	74	33	30	22					
		8	74	33	30	22					
		10	74	33	30	22					
		12	79	36	32	22					
		15	79	36	32	24					
		18	79	36	32	24					
		20	79	36	32	24					
		25	79	36	32	24					
		30	84	38	34	31					
		35	87	39	35	33					
		40	94	42	40	39					
CBE 5-6	全ねじ	6	94	42	38	25					
		8	74	33	30	22					
		10	74	33	30	22					
		12	74	33	30	22					
		15	79	36	32	24					
		18	79	36	32	24					
		20	79	36	32	24					
		25	79	36	32	24					
		30	84	38	34	31					
		35	87	39	35	33					
		40	94	42	40	39					
		45	94	42	40	39					
CBE 5-8	全ねじ	8	94	42	38	25					
		10	74	33	30	22					
		12	74	33	30	22					
		15	79	36	32	24					
		18	79	36	32	24					
		20	79	36	32	24					
		25	79	36	32	24					
		30	84	38	34	31					
		35	87	39	35	33					
		40	94	42	40	39					
		45	94	42	40	39					
		50	94	42	40	39					

型式	ℓ	¥基準単価				¥スライド単価					
		Type M-L	1~9本	10~19本	20~49本	50本以上	Type M-L	1~9本	10~19本	20~49本	50本以上
CBE 5-15	全ねじ	15	74	33	30	24					
		18	79	36	32	28					
		20	79	36	32	28					
		25	79	36	32	28					
CBE 6-8	全ねじ	8	89	40	36	24					
		10	74	33	30	24					
		12	74	33	30	24					
		15	74	33	30	24					
CBE 6-10	全ねじ	10	89	40	36	24					
		12	74	33	30	24					
		15	74	33	30	24					
		18	79	36	32	28					
		20	79	36	32	28					
		25	79	36	32	28					
		30	87	39	35	33					
		35	94	42	41	39					
		40	99	45	44	43					
		45	105	52	51	50					
		50	110	56	55	54					
		CBE 8-10	全ねじ	10	110	54	53	52			
12	94			42	41	39					
15	94			42	41	39					
18	94			42	41	39					
20	94			42	41	39					
25	99			45	44	43					
30	99			45	44	43					
35	110			57	56	55					
40	115			63	62	61					
45	115			67	66	65					
50	125			89	88	87					
55	125			110	109	108					

型式	ℓ	¥基準単価				¥スライド単価							
		Type M-L	1~9本	10~19本	20~49本	50本以上	Type M-L	1~9本	10~19本	20~49本	50本以上		
CBE 8-60	全ねじ	60	135	132	131	130							
		65	155	142	141	140							
		70	175	150	145	140							
		75	200	160	150	140							
CBE 10-15	全ねじ	15	120	68	66	65							
		20	120	68	66	65							
		25	120	68	66	65							
		30	130	75	70	69							
CBE 12-15	全ねじ	15	140	84	75	72							
		40	150	90	80	74							
		45	160	96	85	80							
		50	190	114	90	80							
		55	190	114	90	87							
		60	200	120	95	87							
		65	200	120	110	100							
		70	200	120	110	100							
		75	200	120	110	100							
		CBE 12-20	全ねじ	20	170	119	90	75					
				25	170	119	90	77					
				30	190	133	100	80					
35	210			147	110	85							
40	240			168	120	89							
45	260			182	125	92							
50	280			196	130	98							
55	300			210	140	100							
60	330			231	150	108							

Order 注文例 **型式 CBE4-10**

Delivery 出荷日 **在庫品** 翌日出荷 **P89**
 *ご希望によりPM5:00迄、当日出荷受付致します。

六角穴付ボルト(パック販売)/六角穴付ボルト

—三価クロメート/ユニクロメッキ—



CADデータフォルダ名: 35_Screws

RoHS **PACK-SCBE**

M 材質 SCM435
S 表面処理 三価クロメート
H 硬度 HRC32~39
 ※強度区分 10.9

CBM **CBM1はRoHS非対応**

M 材質 SCM435
S 表面処理 ユニクロメッキ
H 硬度 HRC32~39
 ※強度区分 10.9

型式	ℓ	PACK-SCBE		PACK-SCBE		
		パック入数	単価	単価	単価	
PACK-2-5 SCBE	全ねじ	2-5	1,500	900		
		6-8			1,190	710
		10				
		12				
		15				
		20				
		25				
		30				
		35				
		40				
PACK-2.6-5 SCBE	全ねじ	2.6-5	1,480	880		
		6-8			1,370	820
		10			1,610	960
		12			1,910	1,140
		15			2,130	1,260
		20			2,480	1,470
		25				
		30				
		35				
		40				
PACK-3-5 SCBE	全ねじ	3-5	1,100	680		
		6-8	940	560		
		10			2,690	1,600
		12				
		15				
		20				
		25				
		30				
		35				
		40				
PACK-4-6 SCBE	全ねじ	4-6	1,100	680		
		8-12			1,950	1,180
		15				
		20				
		25				
		30				
		35				
		40				
		45				
		50				
PACK-5-8 SCBE	全ねじ	5-8	1,100	680		
		10			1,740	1,000
		12				
		15				
		20				
		25				
		30				
		35				
		40				
		45				
PACK-6-8 SCBE	全ねじ	6-8	1,100	680		
		10			1,500	900
		12				
		15				
		20				
		25				
		30				
		35				
		40				
		45				
PACK-8-12 SCBE	全ねじ	8-12	1,300	780		
		15			1,380	820
		20			1,440	860
		25			1,480	880
		30				
		35				
		40				
		45				
		50				
		55				
PACK-10-15 SCBE	全ねじ	10-15	1,300	780		
		20			1,540	920
		25			1,600	960
		30			1,700	1,020
		35			1,780	1,060
		40			1,840	1,100
		45			1,950	1,170
		50			2,000	1,200
		55				