

六角穴付ボタンボルト

ご使用数が多い場合には箱販売がお得です。P.157

■六角穴付ボタンボルト

RoHS

Type	材質	硬度	表面処理	強度区分
BCB	SCM435	34~44HRC	四三酸化鉄皮膜	10.9

※ e(不完全ねじ部)=最大2ピッチ

M×P (並目)	A	E	B	C (最小)	d	e
2×0.4	3.5	1.3	1.3	0.6	2.4	0.6
2.5×0.45	4.5	1.5	1.5	0.8	3	0.8
3×0.5	5.7	1.65	2	1.04	3.6	1
4×0.7	7.6	2.2	2.5	1.3	4.7	1.4
5×0.8	9.5	2.75	3	1.56	5.7	1.6
6×1.0	10.5	3.3	4	2.08	6.8	2
8×1.25	14.0	4.4	5	2.6	9.2	2.5
10×1.5	17.5	5.5	6	3.12	11.2	3.0

※強度区分とは、ネジの引張強さです。
(例)10.9
降伏点または耐力の最小値が引張強さの90%であることを示します。
引張強さの最小値が1040N/mm²であることを示します。

■BCB

型式	¥基準単価		¥スライド単価			
	Type	M-L	1~199本	200~299本	300~499本	500本以上
BCB	2-3	3	85	56	46	30
		4	85	56	46	30
		5	85	48	38	22
		6	85	52	42	26
		8	85	54	44	28
	2.5-4	4	75	50	40	24
		5	75	50	40	24
		6	75	50	40	24
		8	75	50	40	24
		10	85	56	46	30
	3-4	4	50	46	19	16
		5	26	23	11	8
		6	26	23	11	7
		8	26	23	11	7
		10	26	23	11	7
12		26	23	11	7	
15		26	23	11	8	
20		31	28	13	10	
25		34	31	15	12	
4-6		6	26	23	11	7
	8	26	23	11	7	
	10	26	23	11	7	
	12	26	23	11	7	
	15	26	23	11	7	
	20	36	33	15	9	
	25	40	36	16	10	
	30	45	41	19	11	
	5-6	6	27	24	11	7
		8	27	24	11	7
10		27	24	11	7	

型式	¥基準単価		¥スライド単価			
	Type	M-L	1~199本	200~299本	300~499本	500本以上
BCB	5-12	12	27	24	11	7
		15	32	29	13	8
		20	36	33	15	10
		25	40	36	16	11
		30	45	41	19	12
		35	54	49	20	15
	6-8	8	37	34	14	9
		10	36	33	13	9
		12	36	33	13	9
		15	40	36	15	9
		20	40	36	15	10
		25	44	40	16	11
		30	50	46	19	11
		35	54	49	20	15
		8-10	10	55	45	16
12			55	45	16	14
15	48		44	16	14	
20	53		48	18	15	
25	55		50	19	16	
30	59		54	20	17	
35	66		60	22	20	
40	75		69	26	21	
45	81		74	28	23	
50	88		81	31	26	
10-15	15	150	55	38	30	
	20	130	50	29	25	
	25	130	50	31	26	
	30	140	55	33	30	
	35	150	55	35	31	
40	160	55	38	33		

■六角穴付ボタンボルト—ステンレス—

RoHS

Type	材質	硬度	表面処理	強度区分
SBCB	SUS304相当	-	-	A2-50

※ e(不完全ねじ部)=最大2ピッチ

M×P (並目)	A	E	B	C (最小)	d	e
2×0.4	3.5	1.3	1.3	0.6	2.4	0.6
2.5×0.45	4.5	1.5	1.5	0.8	3	0.8
3×0.5	5.7	1.65	2	1.04	3.6	1
4×0.7	7.6	2.2	2.5	1.3	4.7	1.4
5×0.8	9.5	2.75	3	1.56	5.7	1.6
6×1.0	10.5	3.3	4	2.08	6.8	2
8×1.25	14.0	4.4	5	2.6	9.2	2.5

※強度区分とは、ネジの引張強さです。
(例)A2-50
引張強さの最小値が500N/mm²であることを示します。
鋼種区分がA2(オーステナイト系ステンレス)

■SBCB

型式	¥基準単価		¥スライド単価				
	Type	M-L	1~199本	200~299本	300~499本	500本以上	
SBCB	2-3	3	90	70	60	40	
		4	90	70	60	40	
		5	90	70	60	40	
		6	90	70	60	40	
		2.5-4	4	80	60	50	40
			5	80	60	50	38
	6		80	60	50	38	
	3-4	4	60	50	45	42	
		5	29	26	23	20	
		6	29	26	23	20	
		8	29	26	23	20	
		10	29	26	23	20	
		12	29	26	23	20	
		15	29	26	23	20	
		20	36	32	28	24	
25		42	37	33	29		
4-6	6	29	26	23	19		
	8	29	26	23	19		
	10	29	26	23	19		
	12	29	26	23	19		
	15	29	26	23	19		
	20	36	32	28	22		
	25	42	37	33	27		
	30	53	47	42	32		
	5-6	6	43	38	34	30	

型式	¥基準単価		¥スライド単価			
	Type	M-L	1~199本	200~299本	300~499本	500本以上
SBCB	5-8	8	41	36	32	28
		10	36	32	28	24
		12	36	32	28	24
		15	39	35	31	27
		20	43	38	34	29
		25	47	42	37	32
	6-8	8	47	42	37	30
		10	46	41	36	30
		12	46	41	36	30
		15	49	44	39	31
		20	55	49	43	32
		25	61	54	48	33
		30	72	64	57	35
		35	80	71	63	38
		8-10	10	88	78	70
12	88		78	70	61	
15	87		78	68	60	
20	92		79	70	60	
25	97		82	75	60	
30	100		85	80	60	
40	40	120	98	90	60	
	45	135	105	90	60	
	50	148	110	90	60	

35
ナット・座金



Order
注文例

型式
BCB4-10
SBCB5-10



Delivery
出荷日

在庫品

翌日出荷 P.89

ご希望によりPM5:00迄、当日出荷受付致します。