



Dps	l	M	N	型式		L	¥基準単価
				Type	Dps		
25	-0.007 -0.020	10	5	4	CLKGH	50~150	1,190
						151~300	1,670
30	-0.009 -0.025	10	5	5	CLKGH	50~150	1,630
						151~300	2,120
35	-0.009 -0.025	10	5	5	CLKGH	80~150	1,920
						151~300	2,550
40	-0.009 -0.025	10	5	5	CLKGH	301~400	3,140
						80~150	2,310
45	-0.009 -0.025	10	5	5	CLKGH	151~300	3,160
						301~400	3,960
50	-0.009 -0.025	10	5	5	CLKGH	100~150	2,790
						151~300	3,850
50	-0.009 -0.025	10	5	5	CLKGH	301~500	5,220
						100~150	3,460
50	-0.009 -0.025	10	5	5	CLKGH	151~300	4,750
						301~500	6,510

Order 注文例 型式 - L
 CLKGH 30 - 157

Delivery 出荷日 3 日目発送

在庫品 翌日出荷 P.37

数量スライド価格 (1円未満切り捨て) P.37

数量 1~9 10~19 20~29 30~50 表示数量超えは
 値引率 基準単価 5% 10% 15% 価格・出荷日お見積り



D1	d	ばね定数 N/mm [kgf/mm]	F max N [kgf]	最大荷重 N [kgf]	初張力 N [kgf]	型式		¥基準単価
						Type	D - L	
21 (±0.4)	2	0.95 [0.097]	55.22	61.98 [6.32]	9.22 [0.94]	AWL25	68	400
		0.60 [0.061]	87.94				83	420
		0.39 [0.040]	132.93				105	440
		0.25 [0.026]	210.64				143	490
		0.16 [0.016]	333.34				203	600
26.8 (±0.5)	2.6	1.30 [0.133]	64.94	101.40 [10.34]	16.57 [1.69]	AWL32	86.1	630
		0.82 [0.084]	103.42				106.5	660
		0.54 [0.055]	156.33				135.5	700
		0.34 [0.035]	247.72				184.9	750
		0.22 [0.022]	392.02				262.9	900
19.8 (±0.4)	2.6	2.95 [0.301]	35.10	132.39 [13.50]	28.73 [2.93]	AWM25	72.1	490
		1.86 [0.190]	55.90				92.5	510
		1.23 [0.125]	84.50				121.5	550
		0.77 [0.079]	133.90				170.9	600
		0.49 [0.050]	211.90				248.9	660
25.6 (±0.5)	3.2	3.19 [0.325]	45.50	184.66 [18.83]	39.42 [4.02]	AWM32	91.2	700
		2.00 [0.204]	72.46				116.8	720
		1.32 [0.135]	109.53				152.0	800
		0.83 [0.085]	173.56				212.8	870
		0.53 [0.054]	274.66				308.8	940



A	B	C	D	E	T	型式		¥基準単価
						Type	No.	
20	35	18	6.5	13	4.5	HK	7	760
							8	
25	40	20						

S	W	MxP	l	型式		L	¥基準単価
				Type	D		
8	14	12x1.75	24	SSPO	16	12 15 18	390
					20		550
					25		720
10	22	20x2.5	40	WSPO	16	25 30 35	420
					20		610
					25		770

Order 注文例 型式 - L
 SSPO 20 - 15
 HK 7

Delivery 出荷日 在庫品 翌日出荷 P.37

数量スライド価格 (1円未満切り捨て) P.37

数量 1~19 20~49 50~99 100~200 表示数量超えは
 値引率 基準単価 5% 10% 15% 価格・出荷日お見積り



D1	d	ばね定数 N/mm [kgf/mm]	F max N [kgf]	最大荷重 N [kgf]	初張力 N [kgf]	型式		¥基準単価
						Type	D - L	
18.6 (±0.4)	3.2	7.37 [0.752]	23.76	242.22 [24.70]	67.08 [6.84]	AWH25	77.2	530
		4.63 [0.472]	37.84				102.8	570
		3.06 [0.312]	57.20				138.0	600
		1.93 [0.197]	90.64				198.8	640
		1.22 [0.124]	143.44				294.8	750
26.8 (±0.5)	4	8.48 [0.865]	29.97	353.53 [36.05]	99.44 [10.14]	AWH32	98	820
		5.33 [0.543]	47.73				130	1,020
		3.52 [0.359]	72.15				174	1,080
		2.23 [0.227]	114.33				250	1,160
		1.40 [0.143]	180.93				370	1,380
19.8 (±0.4)	4	20.00 [2.040]	15.26	466.99 [47.62]	161.91 [16.51]	AWB25	84	830
		12.55 [1.280]	24.30				116	900
		8.31 [0.847]	36.73				160	980
		5.25 [0.535]	58.20				236	1,050
		3.31 [0.338]	92.10				356	1,240



D1	d	ばね定数 N/mm [kgf/mm]	F max N [kgf]	最大荷重 N [kgf]	初張力 N [kgf]	型式		¥基準単価
						Type	D - L	
17 (±0.4)	4	20.00 [2.040]	15.26	466.99 [47.62]	161.91 [16.51]	AWB25	84	830
		12.55 [1.280]	24.30				116	900
		8.31 [0.847]	36.73				160	980
		5.25 [0.535]	58.20				236	1,050
		3.31 [0.338]	92.10				356	1,240



線径 d	ばね定数 N/mm [kgf/mm]	F=L×23%		F=L×25%		初張力 N [kgf]	識別色	型式		
		Fmm	N [kgf]	Fmm	N [kgf]			Type	D - L	
5.0	12.55 [1.28]	42.1	703.1 [71.7]	45.7	748.3 [76.3]	174.8 [17.84]	茶 赤 黒 黄 水色	AWK	34-183	1,850
	10.91 [1.11]	45.5	671.2 [68.3]	49.5	714.8 [72.8]				198	1,930
	10.04 [1.03]	47.8	654.7 [67.1]	52.0	696.9 [71.4]				208	2,000
	9.30 [0.95]	50.1	640.7 [65.4]	54.5	681.6 [69.6]				218	2,080
	8.66 [0.88]	52.4	628.6 [64.0]	57.0	668.4 [68.0]				228	2,160

■引張ばね

●荷重 [kgf] = 荷重 N × 0.101972
 ◎初張力は参考値です。
 ◎kgf = N × 0.101972

■引張ばね用リング

■特長
 ③フック部と①コイルスプリング部が別になっている為、バネの可動による自転運動や偏荷重による疲労破壊に強く、②コマ部() になっています。
 ①コイルスプリング部と②コマ部は線接触となり、高耐久性を実現しました。

Order 注文例 型式
 AWL25-105
 AWK34-183
 BSR4-40

Delivery 出荷日 在庫品 翌日出荷 P.37

数量スライド価格 (1円未満切り捨て) P.37

数量 1~19 20~49 50~99 100~200 表示数量超えは
 値引率 基準単価 5% 10% 15%