

MATERIAL SAFETY DATA SHEET

FEB.10, 2016

1. PRODUCT AND COMPANY IDENTIFICATION

-Product Name : M-GSMOS

-Product Use : Lubricating Grease

-Supplier

Mold Components Division, MISUMI Die & Mold Business Company, MISUMI Corporation

Iidabashi First Bldg., 5-1, Koraku 2-chome, Bunkyo-ku, Tokyo 112-8583, Japan

TEL: +81-3-5805-7190

FAX: +81-3-5805-7191

Administrative Number: M-GS1130_ENG

2. CONPOSITION / INFORMATION ON INGREDIENTS

Substance/mixture : Mixture

Component	% By Weight	CAS Number
Refined Mineral Oil	90.0	-----
Oxidation Stabilizer	5.0	-----
Molybdenum Disulfide	5.0	-----

3. HAZARDS IDENTIFICATION

Classification: Dose not correspond to classification standards.

Dangerousness: N/A

Toxicity: Unknown

Environmental Impact: Unknown

PRTR Law: Type 1 No.346 Substance Molybdenum compound
Contain 5g per 100g of M-GSMOS.

4. FIRST AID MEASURES

Eyes: Flush eyes, including under the eyelids, with large amount of water.
If irritation persists, seek medical attention.

Skin: Wash thoroughly with mild soap and water. Receive treatment from doctor if necessary.

Ingestion: Give copious amount of water or preferably milk and seek medical attention.

Inhalation: Remove to fresh air. Seek medical attention if symptoms persist.

5. FIRE FIGHTING MEASURES

Cut off combustion source to the fire and extinguish it using a fire extinguishing agent. Also, cool down nearby tanks, building, etc., using a water spray to prevent the fire is forming & spreading. Extinguish the fire fore windward and wear a respirator as necessary.

Flush Point: >200°C

Auto-Ignition Temp: No Data

Flammable Limits LFL: Yes

Unusual Fire & Explosive Hazards: Vapors are heavier than air and can travel along the ground to remote ignition source.

Fire Fighting Equipment: Self-contained breathing apparatus and protective clothing should be worn in fighting fires involving chemicals.

Additional Notes: N/A

6. ACCIDENTAL RELEASE MEASURES

In case of small amount of leakage, collect it in an empty container by Absorbing with earth or sand and wash off the remains with a large amount of water. In case of large amount of leakage, prevent it from flowing with earth or and, lead it to a safe place, cover the surface with form, etc. And, if possible, collect it in a container. Wash off the remains with large amounts of water. In this case, make sure that it should not be brained to a river, etc.

7. HANDLING AND STORAGE

Handling: Wear protective gear to avoid inhalation and prevent it from coming in contact with eyes, skin or clothing. Work from windward if possible. Keep it away from high temperature substances, spark or flame. Prevent if it's from coming in contact with strong acid chemicals. Take measures against static electricity and wear conductive work clothing and shoes. Use up all before disposing of it. Keep children away from the work site.

Storage: Avoid direct sunlight and store it where temperature dose not rise over 40°C.

Do not allow oxidizing or organic hyperacid substances nearby.

Transportation: Use a container which can prevent temperature from rising over 40°C.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory Protection: Organic Vapor type.
Ventilation: Local exhaust, Mechanical type.
Protective Glove: Rubber or Plastic recommended.
Eye Protection: Chemical workers goggles.
Wear: Long sleeve clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Black gray	Odor:	Mild
Physical State:	Paste		
Vapor Pressure:	No data	Boiling Point:	No data
Vapor Density:	No data		
Solubility in Water:	Not soluble	Specific gravity:	0.90(25°C)
Evaporation Rate:	Not determined	Melting point:	No data

10. STABILITY AND REACTIVITY

Stability: This product is stable under all normal condition of storage.
Hazardous polymerization will not occur.
Incompatibility: Oxidizing material can cause a reaction.
Hazardous Decomposition Products: None

11. TOXICOLOGICAL INFORMATION

Toxicological Information: No experimental toxicological data on the preparation as such is available.

12. ECOLOGICAL INFORMATION

Ecological Information: No data on possible environmental effects have been found.

13. DISPOSAL CONSIDERATION

Disposal Methods: Spilled material, unused contents and empty containers must be disposed of in accordance with local, state and federal regulations.

14. TRANSEPORT INFORMATION

DOT Hazard Class: Not Regulated

SEA Transport: Not Regulated

AIR Transport: Not Regulated

15. REGULATORY INFORMATION

US Federal Regulations: Clean air act

SARA Hazard Categories: None

Regulatory Status: Not a controlled product

PRTR Law: With 5% Molybdenum Disulfide (Type 1, No-346)

16. OTHER INFORMATION

All reasonable care has been taken in the preparation of the information contained herein, the manufacturer extend no warranties, makes no makes representation and assumes no responsibility as to the accuracy or suitability of such information for application to purchaser's intended purposes or for consequences of its use.