

# Intel<sup>®</sup> 6300ESB I/O Controller Watchdog Timer Application Programming Interface

Ref. No. 0.3

Copyright © Intel Corporation 2004

intel<sup>®</sup>



INFORMATION IN THIS DOCUMENT IS PROVIDED IN CONNECTION WITH INTEL® PRODUCTS. NO LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE, TO ANY INTELLECTUAL PROPERTY RIGHTS IS GRANTED BY THIS DOCUMENT. EXCEPT AS PROVIDED IN INTEL'S TERMS AND CONDITIONS OF SALE FOR SUCH PRODUCTS, INTEL ASSUMES NO LIABILITY WHATSOEVER, AND INTEL DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY, RELATING TO SALE AND/OR USE OF INTEL PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT. Intel products are not intended for use in medical, life saving, life sustaining applications.

Intel may make changes to specifications and product descriptions at any time, without notice.

Designers must not rely on the absence or characteristics of any features or instructions marked "reserved" or "undefined." Intel reserves these for future definition and shall have no responsibility whatsoever for conflicts or incompatibilities arising from future changes to them.

The Intel Watchdog Timer Application Programming Interface may contain design defects or errors known as errata which may cause the product to deviate from published specifications. Current characterized errata are available on request.

MPEG is an international standard for video compression/decompression promoted by ISO. Implementations of MPEG CODECs, or MPEG enabled platforms may require licenses from various entities, including Intel Corporation.

This Datasheet as well as the software described in it is furnished under license and may only be used or copied in accordance with the terms of the license. The information in this manual is furnished for informational use only, is subject to change without notice, and should not be construed as a commitment by Intel Corporation. Intel Corporation assumes no responsibility or liability for any errors or inaccuracies that may appear in this document or any software that may be provided in association with this document.

Except as permitted by such license, no part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means without the express written consent of Intel Corporation.

Contact your local Intel sales office or your distributor to obtain the latest specifications and before placing your product order.

Copies of documents which have an ordering number and are referenced in this document, or other Intel literature may be obtained by calling

1-800-548-4725 or by visiting Intel's website at <http://www.intel.com>.

AnyPoint, AppChoice, BoardWatch, BunnyPeople, CablePort, Celeron, Chips, CT Media, Dialogic, DM3, EtherExpress, ETOX, FlashFile, i386, i486, i960, iCOMP, InstantIP, Intel, Intel Centrino, Intel logo, Intel386, Intel486, Intel740, IntelDX2, IntelDX4, IntelSX2, Intel Create & Share, Intel GigaBlade, Intel InBusiness, Intel Inside, Intel Inside logo, Intel NetBurst, Intel NetMerge, Intel NetStructure, Intel Play, Intel Play logo, Intel SingleDriver, Intel SpeedStep, Intel StrataFlash, Intel TeamStation, Intel Xeon, Intel XScale, IPLink, Itanium, MCS, MMX, MMX logo, Optimizer logo, OverDrive, Paragon, PC Dads, PC Parents, PDCharm, Pentium, Pentium II Xeon, Pentium III Xeon, Performance at Your Command, RemoteExpress, SmartDie, Solutions960, Sound Mark, StorageExpress, The Computer Inside., The Journey Inside, TokenExpress, VoiceBrick, VTune, and Xircom are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries.

\*Other names and brands may be claimed as the property of others.


Copyright © 2004, Intel Corporation

## Watchdog Timer Windows API

The following documentation details the method of programmatically controlling the Intel® 6300ESB I/O Controller Watchdog Timer (WDT) device on the Microsoft Windows 2000\*, Windows XP\*, and .NET\* server platforms. The Application Programming Interface (API) presented is for programs written using C\C++ language. To access the WDT API, link the iwdtlib.lib file with your project. All of the defines, structure definitions and function prototypes are included in the header file iwdt.h.

### How the API Works

The API provides a user mode (Ring 3) interface to the watchdog timer driver **iwdtlib.sys**. The functions are exported from the dynamic link library **iwdtlib.dll** and act as a wrapper to the driver's IOCTL-based interface. While it is possible to control the WDT device by directly issuing device I/O function calls, the libraries API will greatly simplify the process of working with the WDT.





## Interfacing the API Library to Your Code

The following lines would be added to your project to access the WDT timer functions.

```
extern "C" WDT_IMPORT HANDLE WdtInitLibrary(PWDT);
extern "C" WDT_IMPORT HANDLE WdtGetDeviceHandle();
extern "C" HANDLE WdtGetStatus( HANDLE wdHandle, SAWD_CTRL *WdtStatus );
extern "C" WDT_IMPORT ULONG WdtGetDriverVersion(HANDLE);
extern "C" WDT_IMPORT ULONG WdtGetLibraryVersion(VOID);
extern "C" WDT_IMPORT bool WdtGetCapabilities(HANDLE );
extern "C" WDT_IMPORT bool WdtSetPreloadValues(HANDLE,WDT);
extern "C" WDT_IMPORT bool WdtPing(HANDLE,ULONG);
extern "C" WDT_IMPORT bool WdtEnable(HANDLE, bool);
extern "C" WDT_IMPORT bool WdtLockDevice(HANDLE);
extern "C" WDT_IMPORT bool WdtStageOneNotify(HANDLE, S1FUNCTPTR );
extern "C" WDT_IMPORT BOOL WdtCancelNotify();
extern "C" WDT_IMPORT int WdtCheckTimeOutStatus(HANDLE, BOOL);
extern "C" WDT_IMPORT BOOL WdtSetPrescaler(HANDLE, ULONG);
extern "C" WDT_IMPORT BOOL WdtInterruptConnect(HANDLE, ULONG);
extern "C" WDT_IMPORT BOOL WdtRouteInterrupt(HANDLE, ULONG);
extern "C" WDT_IMPORT BOOL WdtSetMode(HANDLE xhndFile, ULONG);
extern "C" WDT_IMPORT BOOL WdtSetOutputEnable(HANDLE, ULONG);
```

NOTE: Extern "C" forces the use of the C naming convention for non C++ functions, you can omit extern "C" if your program is written in C++. The "WDT\_IMPORT" is a macro defined in the **iwdtlib.h** file that resolves to the string `__declspec(dllimport)`.

Be aware of compiler switches **/Tc** or **/TP**, which tell the compiler to ignore the filename extension and compile the file as C or C++, respectively.



Click a hyperlink below for details on a specific API.

[WdtInitLibrary](#)

[WdtGetDeviceHandle](#)

[WdtGetStatus](#)

[WdtGetDriverVersion](#)

[WdtGetLibraryVersion](#)

[WdtEnable](#)

[WdtGetCapabilities](#)

[WdtLockDevice](#)

[WdtSetPreloadValues](#)

[WdtPing](#)

[WdtConfigure](#)

[WdtSetMode](#)

[WdtStageOneNotify](#)

[WdtCancelNotify](#)

[WdtSetPresecaler](#)

[WdtInterruptConnect](#)

[WdtRouteInterrupt](#)

[WdtSetOutputEnable](#)

[WdtReadPreloadValues](#)

[WdtCheckTimeOutStatus](#)



## WdtInitLibrary

Initializes the watchdog device library and returns a device handle to the caller.

```
HANDLE WdtInitLibrary(  
    PWDT wdtobject  
);
```

### Parameters

*wdtobject*

[in] pointer to a [WDT structure](#).

### Return Value

If the function succeeds, the return value is an open handle to the WDT.

If the function fails, the return value is NULL.

### Remarks

Use the **WdtCloseHandle** function to close an object handle returned by **WdtInitLibrary**. The **WdtInitLibrary** function does the following:

Presets the user mode WDT structure.

Returns a valid driver handle to the caller.

Sets up a soft link between the watchdogs' kernel mode driver and a user supplied function.

This link is required by the **WdtStageOneNotify** function to process the user callback.

### Requirements

#### Windows NT/2000/XP

**Header:** Declared in iwdt.h;.

**Library:** Use Iwdt.lib.

#### Example

```
// A  
HANDLE wdHandle;  
WDT HR_wDt;  
  
wdHandle = WdtInitLibrary(&HR_wDt);
```



## WdtGetDeviceHandle (Obsolete)

Opens the watchdog device and returns a valid device handle to the caller. This function has been replaced by the [WdtInitLibrary](#).

```
HANDLE WdtGetDeviceHandle();
```

### Parameters

*No Parameters*

### Return Value

If the function succeeds, the return value is an open handle to the WDT.

If the function fails, the return value is WDT\_FAILURE.

### Remarks

Use the **WdtCloseHandle** function to close an object handle returned by **WdtGetDeviceHandle**.

### Requirements

**Windows NT/2000/XP**

**Header:** Declared in iwdt.h;.

**Library:** Use Iwdt.lib.

### Example

```
// A
HANDLE wdHandle;
wdHandle = WdtGetDeviceHandle();
```



## WdtGetStatus

Queries the WDT device about its status, returning the results to the caller in the [WdtControl](#) structure.

```
HANDLE WdtGetStatus(  
    HANDLE wdHandle,  
    SAWD_CTRL *WdtStatus  
);
```

### Parameters

*wdHandle*

[in] Handle to the device returned by **WdtGetDeviceHandle**.

*wdt*

[out] pointer to structure that is populated with the watchdog status.

### Return Value

If the function succeeds, the return value is WDT\_SUCCESS.

If the function fails, the return value is WDT\_FAILURE.

### Remarks

This function returns the device status bits, configuration register bits and Lock register bits

### Requirements

**Windows NT/2000/XP**

**Header:** Declared in iwdtlib.h;

**Library:** Use iwdtlib.lib.

Example

```
// Query driver for the watchdog timer's status.
```

```
WdtGetStatus(wdHandle, &WdtStatus);
```



## WdtGetDriverVersion

Returns the watchdog drivers version number as an unsigned long.

```
HANDLE WdtGetDriverVersion();
```

### Parameters

*hFile*

[in] Handle to the device returned by **WdtGetDeviceHandle**.

### Return Value

If the function succeeds, the return value is unsigned long composed of a major and minor version code.

If the function fails, the return value is 0x0FFFFFFFFF.

### Remarks

The lower 16 bits represent the minor version, while the upper 16 bits represent the major version number. This same version number is also reported in the [WdtGetCapabilities](#) function in [the SAWD\\_CAPABILITY\\_OUT\\_BUFF](#) structure.

### Requirements

#### Windows NT/2000/XP

**Header:** Declared in iwdtlib.h;.

**Library:** Use iwdtlib.lib.

Example

```
// Query the driver for it version number then format as an ASCII
// string

Char buffer[40];
ULONG   DrvVersion;
USHORT  Lo,Hi;

DrvVersion=WdtGetDriverVersion();
Lo=LOWORD(DrvVersion);
Hi=HIWORD (DrvVersion);

sprintf(buffer, "Driver Version %u.%u",Hi,Lo);
```



## WdtGetLibraryVersion

Returns the watchdog libraries version number as an unsigned long.

```
HANDLE WdtGetLibraryVersion();
```

### Parameters

*No Parameters*

### Return Value

The return value is unsigned long composed of a major and minor version code.

### Remarks

The lower 16 bits represent the minor version, while the upper 16 bits represent the major version number.

### Requirements

#### Windows NT/2000/XP

**Header:** Declared in iwdtlib.h;.

**Library:** Use iwdtlib.lib.

Example

```
// Query the library for it version number then format as an ASCII //  
string  
  
Char buffer[40];  
ULONG   LibVersion;  
USHORT  Lo,Hi;  
  
LibVersion=WdtGetLibraryVersion();  
Lo=LOWORD(LibVersion);  
Hi=HIWORD (LibVersion);  
  
sprintf(buffer, "Library Version %u.%u",Hi,Lo);
```



## WdtEnable

Starts or stops the counter depending on the submitted control value.

```

BOOL WdtEnable(
    HANDLE wdHandle,
    BOOL control = TRUE or FALSE,
);

```

### Parameters

*wdHandle*

[in] Handle to the device returned by **WdtGetDeviceHandle**.

*control*

TRUE indicate a request to start the WDT. FALSE indicates a request to stop the WDT.

### Return Value

If the function succeeds, the return value is WDT\_SUCCESS.

If the function fails, the return value is WDT\_FAILURE. To get extended error information

### Remarks

### Requirements

#### Windows NT/2000/XP

**Header:** Declared in iwdtlib.h;.

**Library:** Use iwdtlib.lib.

Example

```

// Start Watchdog timer.
WdtEnable(wdHandle, TRUE);

// Stop Watchdog timer.
WdtEnable(wdHandle, FALSE);

```



## WdtGetCapabilities (Obsolete – Do not use)

Queries the WDT device about its capabilities, returning the results to the caller in the SAWD\_CAPABILITY\_OUT\_BUF structure.

```
HANDLE WdtGetCapabilites(  
    HANDLE wdHandle,  
    SAWD_CAPABILITY_OUT_BUF *WdtCapStruct  
);
```

### Parameters

*wdHandle*

[in] Handle to the device returned by **WdtGetDeviceHandle**.

*wdtCapStruct*

[out] pointer to structure that is populated with the WDT capabilities.

### Return Value

If the function succeeds, the return value is WDT\_SUCCESS.

If the function fails, the return value is WDT\_FAILURE.

### Remarks

This function returns the version number of the driver and the minimum and maximum preload values that can be set.

### Requirements

#### Windows NT/2000/XP

**Header:** Declared in iwdtlib.h;.

**Library:** Use iwdtlib.lib.

Example

```
// Query driver for the watchdog timer's capabilities  
  
WdtGetCapabilities(wdHandle, &WdtCapStruct);
```



## WdtLockDevice

Locks the watchdog device to prevent any further configuration changes. Also prevents the watchdog device from being stopped or started.

```
HANDLE WdtLockDevice (
    HANDLE wdHandle
);
```

### Parameters

*wdHandle*

[in] Handle to the device returned by **WdtGetDeviceHandle**.

### Return Value

If the function succeeds, the return value is WDT\_SUCCESS.

If the function fails, the return value is WDT\_FAILURE.

### Remarks

Locks the configuration register, i.e., the WDT\_TOUT\_CNF and WDT\_ENABLE bits cannot be changed. This is also a Write-Once bit. It cannot be changed until either the power is cycled or a hard reset occurs.

### Requirements

#### Windows NT/2000/XP

**Header:** Declared in iwdtlib.h;.

**Library:** Use iwdtlib.lib.

### Example

```
// Lock the watchdog timer to prevent any further changes
```

```
BOOL status;
status = WdtLockDevice(wdHandle);
```



## WdtSetPreloadValues

Load preload register 1 and preload register 2.

```
BOOL WdtSetPreload(  
    HANDLE wdHandle,  
    WDT wdtConfig  
);
```

### Parameters

*wdHandle*

[in] Handle to the device returned by **WdtGetDeviceHandle**.

*wdtconfig*

[in] pointer to structure that contains WDT preload values and other configuration values.

### Return Value

If the function succeeds, the return value is WDT\_SUCCESS.

If the function fails, the return value is WDT\_FAILURE.

### Remarks

Loading the preload register does not load the 35 bit down counter and will not prevent the WDT from timing out. Use the [WdtPing](#) function to transfer the preload values to the down counter.

### Requirements

#### Windows NT/2000/XP

**Header:** Declared in iwdtlib.h;.

**Library:** Use iwdtlib.lib.

Example

```
wdConfig.preload1=12323;           // Set preload value # 1  
wdConfig.preload2=12000           // Set preload value # 2
```

```
WdtSetPreload(wdHandle,wdtconfig);
```



## WdtPing

Ping the WDT to prevent the WDT from timing out.

```
HANDLE WdtPing(
    HANDLE wdHandle,
);
```

### Parameters

*wdHandle*

[in] Handle to the device returned by **WdtGetDeviceHandle**.

### Return Value

If the function succeeds, the return value is **WDT\_SUCCESS**.

If the function fails, the return value is **WDT\_FAILURE**.

### Remarks

This function is used to prevent a timeout occurring. During stage 1 this function moves the value in preload register 1 to the 35-bit down counter. During stage 2 this function moves the data from preload register 2 to the 35-bit down counter.

### Requirements

#### **Windows NT/2000/XP**

**Header:** Declared in `iwdtlib.h`.

**Library:** Use `iwdtlib.lib`.

Example

```
// Ping the watchdog timer.
BOOL status;
status = WdtPing(wdHandle);
```



## WdtSetPresecaler

Specify which Presecalar mode of operation is used by the WDT.

```
BOOL WdtSetPresecaler(  
    HANDLE wdHandle,  
    BOOL BitPat  
);
```

### Parameters

*wdHandle*

[in] Handle to the device returned by **WdtGetDeviceHandle**.

*BitPat*

[in] Unsigned long bit pattern defined in the `iwdtlib.h`.

### Return Value

If the function succeeds, the return value is `WDT_SUCCESS`.

If the function fails, the return value is `WDT_FAILURE`.

### Remarks

This function is used to select a Presecalar mode for the WDT's main down counter. There are 2 modes available:

- The default mode specifies that the 20-bit preload value is written into bits 34:15 of the down counter, resulting in a 1 KHz clock.
- The fast mode specifies that the preload value is loaded into bits 24:5 of the down counter, resulting in a 1 MHz clock.

You must specify one of the two defined states, **WDT\_NORMAL\_PRESCALER** or **WDT\_FAST\_PRESCALER**. Any other values will cause the function to fail.

### Requirements

**Windows NT/2000/XP**

**Header:** Declared in `iwdtlib.h`;

**Library:** Use `iwdtlib.lib`.

Example // Set Presecalar to default mode.

```
WdtSetPresecaler(wdHandle, WDT_NORMAL_PRESCALER);
```

```
//Set Presecalar to FAST mode
```

```
WdtSetPresecaler(wdHandle, WDT_FAST_PRESCALER);
```



## WdtInterruptConnect

Manually connects the WDT IRQ to the drivers interrupt service routine.

```

BOOL WdtRouteInterrupt(
    HANDLE wdHandle,
);

```

### Parameters

*wdHandle*

[in] Handle to the device returned by **WdtGetDeviceHandle**.

### Return Value

If the function succeeds, the return value is **WDT\_SUCCESS**.

If the function fails, the return value is **WDT\_FAILURE**.

### Remarks

This function is only needed if Windows is unable to assign INTR resources at driver initialization. Intel® 6300ESB I/O Controller A1 silicon is missing **two** interrupt registers as per PCI spec, Interrupt Pin and Line registers logic and is unable to enumerate the WDT device resources.

### Requirements

#### Windows NT/2000/XP

**Header:** Declared in `iwdtlib.h`;

**Library:** Use `iwdtlib.lib`.

Example // connect the IO-APIC IRQ to the drivers ISR

```

WdtInterruptConnect(wdHandle);

```



## WdtRouteInterrupt

Specify how the WDT should report the occurrence of a stage 1 interrupt.

```
BOOL WdtRouteInterrupt(  
    HANDLE wdHandle,  
    ULONG BitPat  
);
```

### Parameters

*wdHandle*

[in] Handle to the device returned by **WdtGetDeviceHandle**.

*BitPat*

[in] Unsigned long bit pattern defined in the `iwdtlib.h`.

### Return Value

If the function succeeds, the return value is `WDT_SUCCESS`.

If the function fails, the return value is `WDT_FAILURE`.

### Remarks

The WDT supports both IRQ and SMI reporting of timeouts.

You must specify **1** of the **3** defined states,

**WDT\_INTR\_IRQ**, **WDT\_INTR\_SMI** or **WDT\_INTR\_DISABLE**

Any other values will cause the function to fail. **WARNING**, the SMI define is in place to allow the user to verify that the SMI generation works correctly. However, the driver has no capabilities to handle WDT-generated SM interrupts and may result in crashing your platform if the BIOS does not implement a default SMI handler.

### Requirements

**Windows NT/2000/XP**

**Header:** Declared in `iwdtlib.h`;

**Library:** Use `iwdtlib.lib`.

Example // Specify the use of IOAPIC - IRQ.

```
WdtRouteInterrupt(wdHandle, WDT_INTR_IRQ);
```



## WdtSetOutputEnable

Enable or Disable the toggling of the external WDT\_OUTPUT pin.

```
BOOL WdtSetOutEnable(
    HANDLE wdHandle,
    ULONG BitPat
);
```

### Parameters

*wdHandle*

[in] Handle to the device returned by **WdtGetDeviceHandle**.

*BitPat*

[in] Unsigned long bit pattern defined in the iwdtlib.h.

### Return Value

If the function succeeds, the return value is WDT\_SUCCESS.

If the function fails, the return value is WDT\_FAILURE.

### Remarks

This function is used to control whether the WDT\_OUTPUT pin is toggled if the WDT times out. By default this feature is enabled.

You must specify **one of the two** defined states,

**WDT\_ENABLE\_EXT\_OUT** or **WDT\_DISABLE\_EXT\_OUT**

Any other values will cause the function to fail.

### Requirements

**Windows NT/2000/XP**

**Header:** Declared in iwdtlib.h;

**Library:** Use iwdtlib.lib.

Example // Specify that the WDT\_OUTPUT pin is toggled on time out.

```
WdtSetOutEnable(wdHandle, WDT_ENABLE_EXT_OUT);
```



## WdtReadPreloadValue

Read back a preload value.

```
ULONG WdtReadPreloadValue(  
    HANDLE wdHandle,  
    ULONG BitPat  
);
```

### Parameters

*wdHandle*

[in] Handle to the device returned by **WdtGetDeviceHandle**.

*BitPat*

[in] Unsigned long bit pattern defined in the `iwdtlib.h`.

### Return Value

If the function succeeds, the return is the current value in either the first or second preload register as specified in the *BitPat* parameter.

If the function fails, the return value is `WDT_FAILURE`.

### Remarks

This function is useful verifying that the value placed in one or both of the preload registers is correct.

You must specify one of the two defined counters.

### **WDT\_PRELOAD\_1** or **WDT\_PRELOAD\_2**

Any other values will cause the function to fail.

### Requirements

**Windows NT/2000/XP**

**Header:** Declared in `iwdtlib.h`;

**Library:** Use `iwdtlib.lib`.

Example // Read the current value of preload register number 1.

```
ULONG Preload_1=0;
```

```
Preload_1=WdtReadPreloadValue(wdHandle, WDT_PRELOAD_1);
```



## WdtCheckTimeOutStatus

Check if a timeout of the WDT has occurred. Optionally reset the timeout flag if the Boolean *Reset* flag is TRUE.

```
int WdtCheckTimeOutStatus(
    HANDLE wdHandle,
    BOOL Reset
);
```

### Parameters

*wdHandle*

[in] Handle to the device returned by **WdtGetDeviceHandle**.

*BitPat*

[in] Boolean flag, setting to TRUE will reset this bit flag.

### Return Value

If the function succeeds, the return value is a 0 or 1. A 1 indicates that the second stage of the WDT reached zero after the first stage counted down to zero.

If the function fails, the return value is a -1.

### Remarks

This function returns the current setting of the WDT\_TIMEOUT bit in the memory mapped 'Reload Register'. This bit is set to '1' if the 35-bit down counter reaches zero for the second time in a row.

### Requirements

#### Windows NT/2000/XP

**Header:** Declared in iwdtlib.h;.

**Library:** Use iwdtlib.lib.

Example // Check if a time out has occurred, then clear the bit flag to (0).

```
WdtCheckTimeOutStatus(wdHandle, TRUE);
```



## WdtConfigure

Set the configuration bits in the WDT.

```
BOOL WdtConfigure(  
    HANDLE wdHandle,  
    WDT wdtConfig  
);
```

### Parameters

*wdHandle*

[in] Handle to the device returned by **WdtGetDeviceHandle**.

*wdtconfig*

[out] pointer to structure that contains WDT preload values and other configuration values.

### Return Value

If the function succeeds, the return value is **WDT\_SUCCESS**.

If the function fails, the return value is **WDT\_FAILURE**.

### Remarks

This function allows the advanced user to directly set bits in the configuration register. Users of this function are assumed to have detailed knowledge of the Intel® 6300ESB I/O Controller WDT.

### Requirements

#### Windows NT/2000/XP

**Header:** Declared in `iwdt.h`;

**Library:** Use `iwdt.lib`.

### Example

```
/* Configure the watchdog timer to enable toggling of the WDT_OUTPUT_PIN,  
route interrupts to IRQ 10 and select Presecalar 1 for loading the down  
counter.  
*/  
wdtConfig.ConfigReg=WDT_ENABLE_TOGGLE | WDT_INTR_IRQ10 |WDT_PRE_1;
```



```
WdtConfigure(wdHandle,wdtconfig);
```

## WdtSetMode

Sets the device to run in WDT mode or free running mode.

```
BOOL WdtSetMode(
    HANDLE wdHandle,
    ULONG mode
);
```

### Parameters

*wdHandle*

[in] Handle to the device returned by **WdtGetDeviceHandle**.

*mode*

[in] Unsigned long bit pattern defined in the `iwdtlib.h`.

### Return Value

If the function succeeds, the return value is `WDT_SUCCESS`.

If the function fails, the return value is `WDT_FAILURE`.

### Remarks

This function allows you switch the WDT to a free running counter. In free running mode the down counter is automatically loaded every time the decremter reaches zero.

You must specify **one of the two** defined states, `WDT_WATCHDOG_MODE` or `WDT_FREE_RUN_MODE`. Any other values will cause the function to fail.

### Requirements

#### Windows NT/2000/XP

**Header:** Declared in `iwdtlib.h`.

**Library:** Use `iwdtlib.lib`.

#### Example

```
// Set the device to watchdog mode.
WdtSetMode(wdHandle, ENABLE_WDT_MODE);

// Set the device to free running mode
```



```
WdtSetMode(wdHandle, ENABLE_FREE_MODE);
```



## WdtStageOneNotify

Set up a callback to a user-supplied function that will handle interrupt processing when the WDT enters stage 1.

```

BOOL WdtStageOneNotify(
    HANDLE wdHandle,
    S1FUNCTPTR lpHandleIntProc
);

```

### Parameters

*wdHandle*

[in] Handle to the device returned by **WdtGetDeviceHandle**.

*lpHandleIntProc*

[in] Application-defined function that is called by the library.

### Return Value

If the function succeeds, the return value is **WDT\_SUCCESS**.

If the function fails, the return value is **WDT\_FAILURE**.

### Remarks

This function creates a low priority thread that monitors shared user/kernel synchronization object, then returns to the caller. The new thread calls the **WaitForSingleObject** function to wait for the driver to signal that a stage 1 interrupt has occurred.

The function uses a semaphore ‘gate’ to prevent the user from creating multiple instances of the user callback thread, i.e., attempting to call this function after a previous call will result in the function returning a **FALSE** back to the caller. You must first cancel the waiting thread before calling this function again.

Passing a **NULL** for the callback address will terminate a waiting thread

### Requirements

#### Windows NT/2000/XP

**Header:** Declared in **iwdtlib.h**;

**Library:** Use **iwdtlib.lib**.

Example// Assign the user-defined function that the watchdog library will call

```
WdtStageOneNotify(wdHandle, S1FUNCTPTR(Stage1CallBack));
```



## WdtCancelNotify

Cancel CALLBACK notification that was set up using the [WdtStageOneNotify](#) call.

```
BOOL WdtCancelNotify(  
void  
);
```

### Parameters

**No Parameters needed**

### Return Value

If the function succeeds, the return value is WDT\_SUCCESS.

If the function fails, the return value is WDT\_FAILURE.

### Remarks

This function frees the waiting stage 1 monitor thread synchronization object, then returns to the caller. Any new stage interrupt activity will still be serviced by the drivers ISR; however, the user stage 1 function will **not** be called.

### Requirements

**Windows NT/2000/XP**

**Header:** Declared in iwdtlib.h;.

**Library:** Use iwdtlib.lib.

Example// cancel the user-defined function that the watchdog library will call

```
WdtCancelNotify();
```



## Format of Stage One Handler

```
ULONG Stage1CallBack(LPVOID UserData)
{
    ULONG *iData;
    BOOL status=FALSE;
    char buffer[100];

    //
    // User can cast UserData to which every memory type is appropriate
    //

    iData = (ULONG *) UserData;

    //
    // Place code here that will decide what to do if a stage 1
    // Interrupt occurs
    //

return status;
}
```



## Appendix A: Header File Constructs

```
typedef struct WdtControl
{
    bool    Running;           // 0 WDT is idle, 1 WDT is Running
    bool    Mode;             // 0 (default) Run as Watchdog timer, 1 = Free running mode
    bool    Prescalar;        // 0 (default) use 34:15 prescalar setting, 1 = 24:5
    bool    OutputEnable;     // 0 (default) Enable WDT out pin 1 = disable

    ULONG   InterruptRouting; // 00 = IRQ, 01 (Reserved) 10 = SMI 11 = DISABLED
    ULONG   Refresh;          // Number of seconds before WDT must be refreshed
    ULONG   PreLoad1;         // primary down counter value Stage 1
    ULONG   PreLoad2;         // Secondary down counter value Stage 2
    USHORT  ConfigReg;        // Bit pattern to be written to the configuration register
    USHORT  LockReg;          // Bit pattern to be written to the LOCK register
    USHORT  DeviceStatus;     // Bits read from the Device Status register

    HANDLE  wdtHandle;        // copy of the active handle to the device driver
    ULONG   InitStatus;       // Initialization results; 0= OK
    BOOL    ErrorMsgBox;      // TRUE = allow msg box generation, FALSE disable Msg box
    UHSORT  DriverVersionLo;  // lo portion of driver version
    UHSORT  DriverVersionHi;  // Hi portion of driver version
    UHSORT  LibraryVersionLo; // lo portion of Library version
    UHSORT  LibraryVersionHi; // Hi portion of Library version

}WDT, *PWDT;
```

Note: The [WdtInitLibrary](#) function call will initialize the preload registers, set the initial refresh rate to once per second, set the execution flag to 'IDLE' and save off a copy of the drivers handle.

```
typedef struct _SAWD_CAPABILITY_OUT_BUFFER
{
    ULONG Version;           // version of driver used
    ULONG Capability;        // bit field indicating capabilities
    ULONG min;               // minimum value in msec
    ULONG max;               // maximum value in msec

} SAWD_CAPABILITY_OUT_BUFFER, *PSAWD_CAPABILITY_OUT_BUFFER;
```



## Appendix B: Program Defines

### Return constants:

WDT_SUCCESS	Function Passed
WDT_FAILURE	Function Failed

### Input constants:

WDT\_ENABLE  
WDT\_DISABLE

WDT_INTR_IRQ	0x00
WDT_INTR_SMI	0x02
WDT_INTR_DISABLE	0x03
WDT_NORMAL_PRESCALER	0x0FFFFFFB // Bit pattern to set bit 2 to a zero
WDT_FAST_PRESCALER	0x04 // Bit pattern to set bit 2 to a one
WDT_DISABLE_EXT_OUT	0x0FFFFFFD // Bit pattern to set bit 5 to a zero
WDT_ENABLE_EXT_OUT	0x20 // Bit pattern to set bit 5 to a one
WDT_PRELOAD_1	0x01
WDT_PRELOAD_2	0x02
WDT_WATCHDOG_MODE	0x0FFFFFFB // Bit pattern to set bit 2 to a zero
WDT_FREE_RUN_MODE	0x04