

**P.2-1405**<規格表>

A 寸法の数値を修正

型式		呼び	A	C <sub>1</sub>	C <sub>2</sub>	E	二面幅 H	ねじサイズ M	質量 (g)	質量標準値 1~9コ	質量標準値 10~29
Type	D										
ASPSL	4	M5	21	32.1	36.7	12	10	M5×0.8	25.9	4,080	3,540
		1	23	37.9	43.4	14	13	R1/8	41.0	4,120	3,580
	6	M5	22.5	32.1	36.7	12	10	M5×0.8	24.9	4,120	3,580
		1	24.5	37.9	43.4	14	13	R1/8	40.5	4,380	3,810
		2	26	47.1	53.3	17	16	R1/4	73.0	4,930	4,280
		1	26	37.9	43.4	14	13	R1/8	39.2	4,380	3,810
	8	2	27.5	47.1	53.3	17	16	R1/4	71.8	4,920	4,280
		3	29.5	55.1	61.6	22	19	R3/8	133.0	5,840	5,080
	10	2	30	47.1	53.3	17	16	R1/4	70.7	5,000	4,350
		3	32	55.1	61.6	22	19	R3/8	134.0	5,920	5,150
	12	3	33.5	55.1	61.6	22	19	R3/8	129.8	6,340	5,510

<貼り付け用>

型式		呼び	A	C <sub>1</sub>	C <sub>2</sub>	E	二面幅 H	ねじサイズ M	質量 (g)	質量標準値 1~9コ	質量標準値 10~29
Type	D										
ASPSL	4	M5	21	32.1	36.7	12	10	M5×0.8	25.9	4,080	3,540
		1	23	37.9	43.4	14	13	R1/8	41.0	4,120	3,580
	6	M5	22.5	32.1	36.7	12	10	M5×0.8	24.9	4,120	3,580
		1	24.5	37.9	43.4	14	13	R1/8	40.5	4,380	3,810
		2	26	47.1	53.3	17	16	R1/4	73.0	4,930	4,280
		1	26	37.9	43.4	14	13	R1/8	39.2	4,380	3,810
	8	2	27.5	47.1	53.3	17	16	R1/4	71.8	4,920	4,280
		3	29.5	55.1	61.6	22	19	R3/8	133.0	5,840	5,080
	10	2	30	47.1	53.3	17	16	R1/4	70.7	5,000	4,350
		3	32	55.1	61.6	22	19	R3/8	134.0	5,920	5,150
	12	3	33.5	55.1	61.6	22	19	R3/8	129.8	6,340	5,510