

P.935<規格表>

表の注釈を追記しました。

■L寸固定タイプ

型式 Type	D	L 選択	L ₁	N	u	(n)	d	T	H	付属リピン◎			¥基準単価		
										HCMGH	HCMGH	SHCMG	HCMGH	HCMGH	SHCMG
HCMG	3	10 12 14 15 16 18 20	L+ 4.4	2.5	2.9	1.5	0.8	1.5	5.5	NPN0.8-8	NSPN0.8-8	210	220	220	
	L+ 4.5		1												1
HCMGH (焼入タイプ)	5	15 16 18 20 22 24 25 30	L+ 5.6	3.5	4.9	1.5	1.2	1.5	8	NPN1.2-10	NSPN1.2-10	260	270	290	
	L+ 5.8		9												9
SHCMG (ステンレス)	8	18 20 22 24 25 30 35 40 45 50	L+ 7	4	7.8	1.5	2	2	12	NPN2-12	NSPN2-12	360	400	410	
	L+ 8.25		5												5
	12	22 24 25 30 35 40 45 50	L+10.6	6	11.8		3.2	3	17	NPN3.2-20	NSPN3.2-20	420	460	480	

◎ 付属品と同等の型式となります。メンテナンスの際にご参照ください。 ㊦ P.933

■L寸指定タイプ(0.1mm単位)

型式 Type	D	L 指定0.1mm単位	L ₁	N	u	(n)	d	T	H	付属リピン◎			¥基準単価						
										HCLGN	PHCLGN	SHCLGN	HCLGN	HCLGN	PHCLGN	GHCLGN	SHCLGN	SHCLGN	GSCHLGN
HCLGN	3	5.0~50.0	L+ 4.4	2.5	2.9	1.5	0.8	1.5	5.5	NPN0.8-8	NSPN0.8-8	500	660	630	810	1,260	730	940	1,880
	L+ 4.5		1																
HCLGHN	4	10.0~60.0	L+ 5.6	3.5	4.9	1.5	1.2	1.5	8	NPN1.2-10	NSPN1.2-10	570	700	730	910	1,460	850	1,080	2,160
	L+ 5.8		9																
PHCLGN	6	15.0~100.0	L+ 7	4	7.8	1.5	2	12	NPN2-12	NSPN2-12	640	810	810	1,020	1,620	940	1,200	2,400	
	L+ 8.25		5																5
GHCLGN	10	20.0~200.0	L+10.6	6	12.8	1.5	3.2	17	NPN3.2-20	NSPN3.2-20	710	830	1,080	1,360	2,120	1,240	1,580	3,160	
	L+12		7																7
SHCLGN	14	20.0~200.0	L+14.5	8	19.8	1.5	4	20	NPN4-20	NSPN4-20	870	1,120	1,110	1,410	2,220	1,290	1,650	3,300	
	L+15.5		9																9
SHCLGHN	16	20.0~200.0	L+15.5	8	19.8	1.5	4	22	NPN4-25	NSPN4-25	920	1,170	1,160	1,470	2,320	1,340	1,720	3,400	
	L+16.8		9																9
GSCHLGN	17	20.0~200.0	L+17.8	8	21.8	1.5	5	23	NPN5-35	NSPN5-35	970	1,240	1,220	1,560	2,440	1,410	1,820	3,640	
	L+18.8		9																9
	20		L+19.8	8	24.8		5	27			1,110	1,380	1,730	1,970	3,460	2,270	2,500	5,000	

◎ 付属品と同等の型式となります。メンテナンスの際にご参照ください。 ㊦ P.933 ◎ SHCLGN・GSCHLGNは焼入により変色する場合があります。

P.936<規格表>

止め輪型式を下記のように訂正いたします。また、表の注釈を追記しました。

■L寸固定タイプ

型式 Type	D	L 選択	M 許容差	N	u	(n)	d 許容差	T	H	付属止め輪◎			¥基準単価				
										形状	JIS呼び	ほね用鋼	SUS304	HCCG	HCCGH	SHCCG	
HCDG	3	10 12 14 15 16 18 20 22 24 25 30	0.5	+0.05	1.9	1.5	2.9	2	1.5	4.5	E型	No. 2	NETW2	NETWS2	210	220	230
	3																
HCDGH (焼入タイプ)	5	15 16 18 20 22 24 25 30 35 40 45 50	0.7	+0.1	4.9	1.5	5.8	1.5	9	9	E型	No. 4	NETW4	NETWS4	240	260	260
	6																
SHCDG (ステンレス)	8	18 20 22 24 25 30 35 40 45 50	0.9	+0.14	7.8	1.15	7.8	2	12	12	C型	No. 7	NETW7	NETWS7	320	330	380
	10																
	12	22 24 25 30 35 40 45 50			11.8		11.5	-0.11	3	17		No. 12	STWN12	STWS12	380	390	490

◎ 付属品と同等の型式となります。メンテナンスの際にご参照ください。 ㊦ P.931

■L寸指定タイプ(0.1mm単位)

型式 Type	D	L 指定0.1mm単位	M 許容差	N	u	(n)	d 許容差	T	H	付属止め輪◎			¥基準単価									
										形状	JIS呼び	ほね用鋼	SUS304	HCCG	HCCGH	PHCCG	GHCCG	SHCCG	SHCCGH	GSCHCCG		
HCCG	2	5.0~30.0	0.5	+0.05	1.9	1.5	1.5	2	1.5	4.5	E型	No. 1.5	NETW1.5	NETWS1.5	480	600	600	760	1,200	690	890	1,780
	3																					
HCCGH (焼入タイプ)	4	5.0~50.0	2	3.9	3	1.5	3.9	2	1.5	5.5	E型	No. 3	NETW3	NETWS3	500	640	630	800	1,260	730	940	1,880
	5																					
PHCCG	6	10.0~60.0	0.7	+0.1	4.9	1.5	4.9	4	+0.075	8	E型	No. 4	NETW4	NETWS4	570	720	720	910	1,440	830	1,060	2,120
	8																					
GHCCG	10	15.0~100.0	0.9	+0.14	7.8	1.15	7.8	2	12	12	C型	No. 7	NETW7	NETWS7	620	790	790	1,000	1,580	920	1,180	2,360
	12																					
SHCCG	14	20.0~200.0	1.15	+0.14	11.8	1.5	11.8	2	17	17	C型	No. 12	STWN12	STWS12	740	940	970	1,230	1,940	1,150	1,470	2,940
	16																					
SHCCGH (焼入タイプ)	14	20.0~200.0	1.15	+0.14	13.4	1.5	13.4	3	19	19	C型	No. 14	STWN14	STWS14	810	1,030	1,030	1,310	2,060	1,200	1,540	3,080
	15																					
SHCCGH (ステンレス)	16	20.0~200.0	1.35	+0.14	15.2	1.5	15.2	3	21	21	C型	No. 16	STWN16	STWS16	860	1,100	1,100	1,400	2,200	1,380	1,640	3,280
	17																					
GSCHCCG	18	20.0~200.0	1.35	+0.14	17.8	1.5	17.8	3	23	23	C型	No. 17	STWN17	STWS17	880	1,130	1,130	1,440	2,260	1,310	1,690	3,380
	19																					
SHCCGH (焼入タイプ)	20	20.0~200.0	1.35	+0.14	19.8	1.5	19.8	4	26	26	C型	No. 20	STWN20	STWS20	920	1,180	1,180	1,510	2,360	1,380	1,780	3,560
	22																					
	25				23.9		23.9		31	31		No. 25	STWN25	STWS25	1,000	1,250	1,260	1,610	2,520	1,460	1,900	3,800

◎ 付属品と同等の型式となります。メンテナンスの際にご参照ください。 ㊦ P.931 ◎ SHCCGH・GSCHCCGは焼入により変色する場合があります。