

D5のDs7の適用ベアリング外形数値訂正

型式		Ds 選択	適用ベアリング(外径)	B	B1	D1	止めねじ M×長さ	b	¥単価 1~9コ				
Type	D								SCSBR SCSBS	PSCSBR PSCSBS	SSCSBR SSCSBS	SCSSAW SCSSBS	SCSRAB SCSSAB
(ショートノーズタイプ) SCSBR PSCSBR SSCSBR SCSSAW SCSRAB	3	5	673ZZ(6)・683ZZ(7)	8	11	10	M3×3	7	240	320	420	—	—
		6	693ZZ(8)・603ZZ(9)・623ZZ(10)						240	320	420	—	—
	4	7	674ZZ(7)・684ZZ(9)						260	340	440	—	—
		*7	694ZZ(11)・604ZZ(12)・624ZZ(13)						260	340	440	280	330
	5	8	675ZZ(8)						350	400	560	—	—
		*8	685ZZ(11)・695ZZ(13)・605ZZ(14)・625ZZ(16)						350	400	560	350	400
	6	9	676ZZ(10)・686ZZ(13)						350	430	560	—	—
		*9	696ZZ(15)・606ZZ(17)・626ZZ(19)						350	430	560	380	430
	8	11	678ZZ(12)・688ZZ(16)						390	470	610	—	—
		*12	698ZZ(19)・608ZZ(22)・628ZZ(24)						390	470	610	390	440
	10	13	6800ZZ(19)						410	510	660	410	460
		*14	6900ZZ(22)・6000ZZ(26)						410	510	690	410	460
	12	16	6200ZZ(30)・6300ZZ(35)						430	530	690	—	—
		15	6801ZZ(21)						460	560	730	—	—
	15	*16	6901ZZ(24)・6001ZZ(28)						460	560	730	460	510
		*18	6201ZZ(32)・6301ZZ(37)						460	560	730	460	510
	17	*18	6802ZZ(24)・6902ZZ(28)						510	630	820	510	560
*19		6002ZZ(32)	510	630	820	510	560						
20	*21	6202ZZ(35)・6302ZZ(42)	510	630	820	510	560						
	*20	6803ZZ(26)	(560)	(700)	(890)	(560)	(610)						
25	*21	6903ZZ(30)・6003ZZ(35)	(560)	(700)	(890)	(560)	(610)						
	*23	6203ZZ(40)・6303ZZ(47)	(560)	(700)	(890)	(560)	(610)						
30	23	6704ZZ(27)・6804ZZ(32)	600	740	960	—	—						
	*24	6904ZZ(37)	600	740	960	600	650						
35	*27	6004ZZ(42)・6204ZZ(47)	600	740	960	600	650						
	28	6805ZZ(37)	780	960	1,250	—	—						
40	*29	6905ZZ(42)	780	960	1,250	780	830						
	*31	6005ZZ(47)	780	960	1,250	780	830						
45	*32	6205ZZ(52)	780	960	1,250	780	830						
	33	6806ZZ(42)	1,040	1,240	1,630	—	—						
50	35	6906ZZ(47)	1,040	1,240	1,630	—	—						
	*38	6006ZZ(55)・6206ZZ(62)・6306ZZ(72)	1,040	1,240	1,630	1,050	1,100						
55	38	6807ZZ(47)	(1,200)	(1,400)	(1,950)	—	—						
	41	6907ZZ(55)	(1,200)	(1,400)	(1,950)	—	—						
60	43	6007ZZ(62)・6207ZZ(72)	(1,200)	(1,400)	(1,950)	—	—						
	43	6808ZZ(52)	(1,350)	(1,600)	(2,100)	—	—						
65	45	6908ZZ(62)	(1,350)	(1,600)	(2,100)	—	—						
	48	6008ZZ(68)・6208ZZ(80)	(1,350)	(1,600)	(2,100)	—	—						

(アルミ材質品はDs寸法に*印の付いたサイズのみ
寸法に()の付いたサイズはロングノーズタイプのみ)

<訂正用>

適用ベアリング(外径)
673ZZ(6)・683ZZ(7)
693ZZ(8)・603ZZ(9)・623ZZ(10)
674ZZ(7)・684ZZ(9)
694ZZ(11)・604ZZ(12)・624ZZ(13)
675ZZ(8)
685ZZ(11)・695ZZ(13)・605ZZ(14)・625ZZ(16)
676ZZ(10)・686ZZ(13)
696ZZ(15)・606ZZ(17)・626ZZ(19)
678ZZ(12)・688ZZ(16)
698ZZ(19)・608ZZ(22)・628ZZ(24)
6800ZZ(19)
6900ZZ(22)・6000ZZ(26)
6200ZZ(30)・6300ZZ(35)
6801ZZ(21)
6901ZZ(24)・6001ZZ(28)
6201ZZ(32)・6301ZZ(37)
6802ZZ(24)・6902ZZ(28)
6002ZZ(32)
6202ZZ(35)・6302ZZ(42)
6803ZZ(26)
6903ZZ(30)・6003ZZ(35)
6203ZZ(40)・6303ZZ(47)
6704ZZ(27)・6804ZZ(32)
6904ZZ(37)
6004ZZ(42)・6204ZZ(47)
6805ZZ(37)
6905ZZ(42)
6005ZZ(47)
6205ZZ(52)
6806ZZ(42)
6906ZZ(47)
6006ZZ(55)・6206ZZ(62)・6306ZZ(72)
6807ZZ(47)
6907ZZ(55)
6007ZZ(62)・6207ZZ(72)
6808ZZ(52)
6908ZZ(62)
6008ZZ(68)・6208ZZ(80)