

P.678 (規格表)

六角穴ツバ付めねじタイプD18・22のE寸訂正

型式		L 指定0.1mm単位	A	T	B	E	(d)	(N)	M (並目)	¥単価								
Type	D									CLBRM	CLBRHM	PCLBRM	PCLBRHM	GCLBRM	SCLBRM	SCLBRHM	GSCLBRHM	
CLBRM CLBRHM PCLBRM PCLBRHM GCLBRM SCLBRM SCLBRHM GSCLBRHM	6	15.0~100.0	10	5	3	2	5.8	1.5	M 3	400	500	510	640	1,020	630	780	1,560	
	8	20.0~100.0	13		5	3	7.8		M 5	520	620	640	780	1,280	760	950	1,900	
	10	25.0~100.0	16		6	4	9.8		11.8	M 6	600	720	720	890	1,440	850	1,060	2,120
	12	25.0~200.0	18								730	860	890	1,090	1,780	1,050	1,320	2,640
	13	30.0~200.0	24								890	890	1,000	1,140	2,000	1,120	1,390	2,780
	14				8	5	13.8		14.8	M 8	910	940	1,020	1,170	2,040	1,140	1,410	2,820
	15										930	980	1,040	1,200	2,080	1,150	1,430	2,860
	16										M10	950	1,020	1,060	1,240	2,120	1,180	1,470
	17	35.0~200.0	27		1,040	1,120	1,160		1,360	2,320		1,290	1,610	3,220				
	18				1,150	1,260	1,290		1,520	2,580		1,440	1,790	3,580				
	20	40.0~200.0	30		10	6	16.8		17.8	M12	1,230	1,350	1,380	1,630	2,760	1,540	1,920	3,840
	22										1,890	1,810	2,340	2,580	4,680	2,810	3,360	6,720
	25	55.0~200.0	12		8	19.8	21.8		24.8	M16	1,890	1,810	2,340	2,580	4,680	2,810	3,360	6,720
									2,540	2,270	3,300	3,530	6,600	4,070	4,790	9,580		

Ⓜ SCLBRHM・GSCLBRHMは焼入により変色する場合があります。

<訂正用>

