

表記を一部変更

Catalog No.			d	ℓ	L	B	極軽荷重用(PJLSW・PJLSK)		軽荷重用(PJLW・PJLK)		重荷重用(PJHW・PJHK)		極重荷重用(PJXW・PJXK)		¥単価 1~19口	
Type	M(並目)	S					min.	N 荷重	max.	min.	N 荷重	max.	min.	N 荷重		max.
PJLSW PJLW PJHW PJXW	3	1.5	1.0	15	15	0.9	0.12		0.4	0.4	1.3	0.8	2.94	1.1	3.42	900
		3		15	15		0.12		0.4	0.2	1.3	0.6	2.93	0.8	3.41	
	4	2	15	15	1.3	0.27		0.65	0.9	2.0	2.0	8.8	6.1	13.8		
		4	24	24		0.18		0.65	0.6	2.1	1.9	8.75	5.8	13.6		
	5	3	2.0	20	20	1.5	0.4		3	1.4	9.7	2.7	16.3	6.8	22.0	
5		27	27	0.35			3	1.1	10.3	1.0	17.1	5.7	21.5	940		
6	3	2.5	25	25	2	1.8		3.05	6.0	9.8	8.0	26.4	15.8	35.6	900	
	5		30	30		1.5		3.05	3.4	9.86	4.4	26.6	12.9	34.4	970	
8	3	3.1	25	25	2.5	1.9		3.15	6.0	9.9	14.7	27.0	21.9	36.3	1,030	
	5		27	27		1.4		3.15	4.0	9.83	6.7	26.6	14.7	34.5	1,100	
10	5	3.8	30	30	3	1.6		4.6	5.7	14.7	8.2	45.7	24.5	58.6	1,170	
	10		30	43		1.6		4.6	4.4	14.7	6.2	45.1	19.8	58.7	1,320	
12	5	5.5	30	30	4	1.7		4.7	5.8	14.7	18.2	49.0	34.9	63.6	1,430	
	10		35	43		1.6		4.7	5.0	14.7	8.2	49.1	25.5	63.6	1,480	
16	15	8.0	35	51	5	1.8		4.7	6.9	14.7	7.5	48.9	20.1	63.7	1,540	
	10		35	57		2.8		10.8	9.2	34.2	18.9	68.5	38.7	88.4	1,970	
	15		35	57		2.6		10.8	8.6	34.4	14.4	68.6	33.9	88.1		
	20		35	65		2		11	7.1	34.4	4.2	68.6	25.4	88.1	2,310	

①緩み防止の処理はしていません。

②荷重min.は初期荷重、max.はピンを最大限沈めたときの荷重です。

kgf=N×0.101972

<訂正用>

1.0
1.6
2.0
2.5
3.1
3.8
5.5
8.0