

■特長：黒染めタイプを標準品としてご用意しております。




●CADデータフォルダ名：21_Chains_and_Sprockets



RoHS 10

Type	M材質	S表面処理
BSP□□B	S45C相当 (歯先高周波焼入)	四三酸化鉄被膜

A 付属品 セットスクリュー



●歯先とキー溝のスレは±0.5mm

軸穴仕様 **N**
(新JISキー+タップ)
2-M

■適合チェーン選定方法 P.1652

チェーン伝動機構の技術情報 P.2445

型式				軸穴 仕様	軸穴径 (D)																	¥基準単価											
Type	呼び	ボス タイプ	歯数		S仕様	N仕様 (H7) ※は在庫品																	Dp	Do	H	GD	L	ℓ	X	Z	質量 (g)	S仕様 在庫品	N仕様 在庫品以外
BSP	35	B	9	N		—	10 10K	27.85	32	21.5	17	20	6	4.4	60	—	820	920	20	6	4.3	—	22	8	25	10	60	—	820	920			
			10		10 10K* 12*		30.82	34	24.5	20	80				—	820	920	80									—	820	920				
			11		10 10K* 12		33.81	38	27	23	90				—	820	920	90									—	820	920				
			12		10 10K* 12* 14 15* 16* 17*		36.8	41	30.5	26	—				—	850	950	—									—	850	950				
			13		10* 10K 12* 14 15* 16 17		39.8	44	32	29	120				—	850	950	120									—	850	950				
			14		10 10K 12* 14 15* 16 17		42.81	47	32	—	—				—	910	1,010	—									—	910	1,010				
			15		10* 10K 12* 14 15* 16 17 18* 19 20*		45.81	51	35	—	160				—	1,010	1,010	160									—	1,010	1,010				
			16		10 10K 12* 14 15* 16 17* 18 19 20* 22		48.82	54	37	—	190				—	1,000	1,110	190									—	1,000	1,110				
			17		12 14 15 16 17 18 19 20 22 24 25		51.84	57	41	—	220				—	—	1,110	220									—	—	1,110				
			18		12* 14 15* 16* 17 18 19 20* 22 24 25		54.85	60	44	—	250				—	1,040	1,150	250									—	1,040	1,150				
			19		12 14 15 16 17 18 19 20 22 24 25		57.87	63	47	—	280				—	—	1,150	280									—	—	1,150				
			20		12* 14 15* 16 17 18 19 20* 22 24 25* 28 30		60.89	66	50	—	320				—	1,080	1,210	320									—	1,080	1,210				
			21		12 14 15 16 17 18 19 20 22 24 25 28 30		63.91	69	53	—	360				—	—	1,260	360									—	—	1,260				
			22		12* 14 15 16 17 18 19 20 22 24 25 28 30		66.93	72	56	—	370				—	1,130	1,260	370									—	1,130	1,260				
			23		12 14 15 16 17 18 19 20 22 24 25 28 30		69.95	75	60	—	380				—	—	1,300	380									—	—	1,300				
			24		12 14 15 16 17 18 19 20 22 24 25 28 30		72.97	78	—	—	430				—	—	1,300	430									—	—	1,300				
			25		15 16 17 18 19 20 22 24 25 28 30		76	81	—	—	440				—	—	1,300	440									—	—	1,300				
			26		15 16 17 18 19 20 22 24 25 28 30		79.02	84	—	—	450				—	—	1,330	450									—	—	1,330				
			28		15 16 17 18 19 20 22 24 25 28 30		85.07	90	—	—	480				—	—	1,380	480									—	—	1,380				
			30		15 16 17 18 19 20 22 24 25 28 30		91.12	96	53	22	510				—	—	1,450	510									—	—	1,450				
			32		15 16 17 18 19 20 22 24 25 28 30		97.18	102	—	25	540				—	—	1,550	540									—	—	1,550				
			34		20 22 24 25 28 30		103.23	109	—	25	570				—	—	1,730	570									—	—	1,730				
			35		20 22 24 25 28 30		106.26	112	—	25	590				—	—	1,730	590									—	—	1,730				
			36		20 22 24 25 28 30		109.29	115	—	25	610				—	—	1,800	610									—	—	1,800				
			38		20 22 24 25 28 30		115.34	121	63	25	820				—	—	1,930	820									—	—	1,930				
			40		20 22 24 25 28 30		121.4	127	—	25	850				—	—	2,000	850									—	—	2,000				
BSP	40	B	9	N	—	10K 12 14	37.13	42	28	23	5	5.2	6	7.2	25	7	68	28	10	7.2	25	75	110	—	940	940							
			10			10K 12* 14 15* 16 17*	41.1	46	32	27													140	—	840	940							
			11			10K 12* 14 15 16 17 18* 19 20	45.08	51	36	31													190	—	920	1,020							
			12			10K* 12* 14 15* 16 17* 18* 19 20* 22	49.07	55	40	35													220	—	1,020	1,020							
			13			12* 14* 15* 16 17* 18* 19 20* 22	53.07	59	37	—													230	—	950	1,050							
			14			12* 14 15* 16 17 18 19 20* 22 24 25	57.07	63	42	—													280	—	990	1,100							
			15			12 14 15* 16 17 18* 19 20* 22 24 25 28 30	61.08	67	46	—													340	—	990	1,100							
			16			14 15* 16 17 18* 19 20* 22 24 25* 28 30 32	65.1	71	50	—													400	—	1,100	1,100							
			17			14 15 16 17 18 19 20 22 24 25 28 30 32 35	69.12	76	54	—	460	—	—	1,150																			
			18			14 15 16 17 18 19 20* 22 24 25* 28 30 32 35	73.14	80	57	—	510	—	1,100	1,230																			
			19			14 15* 16 17 18 19 20* 22 24 25* 28 30* 32 35 40	77.16	84	62	—	590	—	1,150	1,280																			
			20			14 15 16 17 18 19 20* 22 24 25* 28 30 32 35 40	81.18	88	67	—	760	—	1,240	1,370																			
			21			14 15 16 17 18 19 20 22 24 25 28 30 32 35 40	85.21	92	71	—	850	—	—	1,650																			
			22			14 15 16 17 18 19 20 22 24 25 28 30 32 35 40	89.24	96	75	—	950	—	—	1,660																			
			23			14 15 16 17 18 19 20 22 24 25 28 30 32 35 40	93.27	100	77	—	1000	—	—	1,660																			
			24			14 15 16 17 18 19 20 22 24 25 28 30 32 35 40*	97.3	104	—	25	840	—	1,490	1,660																			
			25			14 17 18 19 20 22 24 25 28 30 32 35 40	101.33	108	63	880	—	—	1,660																				
			26			18 19 20 22 24 25 28 30 32 35 40	105.36	112		920	—	—	1,720																				
			28			20 22 24 25 28 30 32 35 40	113.43	120		1000	—	—	1,850																				
			30			20 22 24 25 28 30 32 35 40	121.5	128		1100	—	—	1,900																				
			32			20 22 24 25 28 30 32 35 40	129.57	137		68	1300	—	—	2,150																			
			34			20 22 24 25 28 30 32 35 40	137.64	145			1400	—	—	2,260																			
			35			20 22 24 25 28 30 32 35 40	141.68	149			1500	—	—	2,300																			
			36			20 22 24 25 28 30 32 35 40	145.72	153			1600	—	—	2,470																			
			38			24 25 28 30 32 35 40	153.79	161	1700		—	—	2,750																				
			40			25 28 30 32 35 40	161.87	169																									