


—全角直角度保証0.1mm単位指定—





型式	材質	硬度
SSFB	S5400	—
SCFB	S50C	—
SCNFB	S50C調質	25±3HRC
SCFF	SUS303	—
SCFS	SUS304	—



$A \pm 0.1$
 (指定0.1mm単位)

$B \pm 0.1$
 (指定0.1mm単位)

$T \pm 0.1$
 (指定0.1mm単位)

⚠ SCNFBは板厚によっては硬度が落ちる場合があります。

6面フライス

0.1mm単位		T 0.1mm単位				
A	B \ T	1.5~9.9			5.0~9.9	
		SSFB	SCFB	SCNFB	SCFF	SCFS
60	10.0~60.0	950	1,020	1,360	1,700	2,300
100		1,000	1,080	1,420	2,090	2,610
60	60.1~100.0	1,000	1,080	1,420	—	—
100		1,110	1,280	1,730	—	—

0.1mm単位		T 0.1mm単位														
A	B \ T	10.0～20.0					20.1～30.0					30.1～40.0				
		SSFB	SCFB	SCNFB	SCFF	SCFS	SSFB	SCFB	SCNFB	SCFF	SCFS	SSFB	SCFB	SCNFB	SCFF	SCFS
10.0～ 60.0	10.0～60.0															
60.1～100.0																
100.1～130.0																
130.1～160.0																
160.1～180.0																
180.1～200.0	20.0～60.0															
200.1～250.0				—					—					—		
250.1～300.0				—					—					—		
300.1～350.0				—					—					—		
350.1～400.0				—					—					—		
400.1～450.0	60.1～100.0			—					—					—		
450.1～500.0				—					—					—		
10.0～ 60.0																
60.1～100.0																
100.1～130.0																
130.1～160.0	100.1～130.0															
160.1～180.0																
180.1～200.0																
200.1～250.0				—					—					—		
250.1～300.0				—					—					—		
300.1～350.0	130.1～160.0			—					—					—		
350.1～400.0				—					—					—		
400.1～450.0				—					—					—		
450.1～500.0				—					—					—		
10.0～ 60.0		160.1～180.0														
60.1～100.0																
100.1～130.0																
130.1～160.0																
160.1～180.0																
180.1～200.0	180.1～200.0															
200.1～250.0				—					—					—		
250.1～300.0				—					—					—		
300.1～350.0				—					—					—		
350.1～400.0				—					—					—		
400.1～450.0				—					—					—		
450.1～500.0				—					—					—		
10.0～ 60.0																
60.1～100.0																
100.1～130.0																
130.1～160.0																
160.1～180.0																
180.1～200.0																
200.1～250.0				—					—					—		
250.1～300.0				—					—					—		
300.1～350.0				—					—					—		
350.1～400.0				—					—					—		
400.1～450.0				—					—					—		
450.1～500.0				—					—					—		
10.0～ 60.0																
60.1～100.0																
100.1～130.0																
130.1～160.0																
160.1～180.0																
180.1～200.0																
200.1～250.0				—					—					—		
250.1～300.0				—					—					—		
300.1～350.0				—					—					—		
350.1～400.0				—					—					—		
400.1～450.0				—					—					—		
450.1～500.0				—					—					—		
10.0～ 60.0																
60.1～100.0																
100.1～130.0																
130.1～160.0																
160.1～180.0																
180.1～200.0																
200.1～250.0				—					—					—		
250.1～300.0				—					—					—		
300.1～350.0				—					—					—		
350.1～400.0				—					—					—		
400.1～450.0				—					—					—		
450.1～500.0				—					—					—		
10.0～ 60.0																
60.1～100.0																
100.1～130.0																
130.1～160.0																
160.1～180.0																
180.1～200.0																
200.1～250.0				—					—					—		
250.1～300.0				—					—					—		
300.1～350.0				—					—					—		
350.1～400.0				—					—					—		
400.1～450.0				—					—					—		
450.1～500.0				—					—					—		
10.0～ 60.0																
60.1～100.0																
100.1～130.0																
130.1～160.0																
160.1～180.0																
180.1～200.0																
200.1～250.0				—					—					—		
250.1～300.0				—					—					—		
300.1～350.0				—					—					—		
350.1～400.0				—					—					—		
400.1～450.0				—					—					—		
450.1～500.0				—					—					—		
10.0～ 60.0																
60.1～100.0																
100.1～130.0																
130.1～160.0																
160.1～180.0																
180.1～200.0																
200.1～250.0				—					—					—		
250.1～300.0				—					—					—		
300.1～350.0				—					—					—		
350.1～400.0				—					—					—		
400.1～450.0				—					—					—		
450.1～500.0				—					—					—		
10.0～ 60.0																
60.1～100.0																
100.1～130.0																
130.1～160.0																
160.1～180.0																
180.1～200.0																
200.1～250.0				—					—					—		
250.1～300.0				—					—					—		
300.1～350.0				—					—					—		
350.1～400.0				—					—					—		
400.1～450.0				—					—					—		
450.1～500.0				—					—					—		
10.0～ 60.0																
60.1～100.0																
100.1～130.0																
130.1～160.0																
160.1～180.0																
180.1～200.0																
200.1～250.0				—					—					—		
250.1～300.0				—					—					—		
300.1～350.0				—					—					—		
350.1～400.0				—					—					—		
400.1～450.0				—					—					—		
450.1～500.0				—					—					—		
10.0～ 60.0																
60.1～100.0																
100.1～130.0																
130.1～160.0																
160.1～180.0																
180.1～200.0																
200.1～250.0				—					—					—		
250.1～300.0				—					—					—		
300.1～350.0				—					—					—		
350.1～400.0				—					—					—		
400.1～450.0				—					—					—		
450.1～500.0				—												

Price
価格 WOSにてご確認ください。

項目	SS400 S50C S50C調質	SUS303 SUS304
板厚平直度 (100mmに対して)	0.02	0.05
平面度 (100mmに対して)	T1.5~7.9	0.1
	T8~15.9	0.07
	T16~	0.05
直角度 (各面)	100mmに対し0.02	
全周面取り	C0.5以下	

[illegible]