

# 六角穴付ボルト



# 小頭六角穴付ボルト

**RoHS** **CB**

各部の寸法・強度区分詳細 **☞** 右ページ  
 材質 SCM435 (M3~M20) **S** 表面処理 四三酸化鉄皮膜 (Fe3O4)  
 SCM440 (M24)  
 硬度 38~43HRC (M3~M20) (ボルト精度 JIS B1176 強度区分 12.9 (M3~M20) 10.9 (M24))  
 ネジ部 JIS B0205の2級

ℓ	型式	標準単価	スライド1	スライド2	スライド3	スライド4
ℓ	型式	標準単価	スライド1	スライド2	スライド3	スライド4
全ねじ Full Thread	CB 3-5					
	6					
	8					
	10					
	12	4		50本	500本	1500本以上
	14			499本	1499本	
	15					
	16					
	18			1本		
	20			49本		
	22					
	25					
	30					
	35					
	40			50本	200本	1000本以上
45			199本	999本		
50						
55						
60			1本			
65			29本			
全ねじ Full Thread	CB 4-5					
	6					
	8					
	10					
	12					
	14	4		50本	500本	1500本以上
	15			499本	1499本	
	16					
	18					
	20			1本		
	22			49本		
	25					
	30					
	35					
	40			50本	200本	1000本以上
45			199本	999本		
50						
55						
60			1本			
65			29本			
70						
75						
全ねじ Full Thread	CB 5-5					
	6					
	8					
	10					
	12					
	14					
	15					
	16					
	18					
	20			50本	200本	1000本以上
	22			199本	999本	
	25					
	30					
	35					
	40			50本	200本	1000本以上
45			199本	999本		
50						
55						
60			1本			
65			49本			
70						
75						
全ねじ Full Thread	CB 8-8					
	10					
	12					
	15					
	16					
	18					
	20					
	22					
	25					
	30					
	35					
	40					
	45					
	50					
	55					
60						
65						
70						
75						

ℓ	型式	標準単価	スライド1	スライド2	スライド3	スライド4	
ℓ	型式	標準単価	スライド1	スライド2	スライド3	スライド4	
全ねじ Full Thread	CB 8-9.5	34					
	100						
	110						
	120						
	130	1本		30本	50本		
	140	29本		49本	以上		
	150						
	160						
	160						
	200	1本		30本	50本		
	233	1本		49本	以上		
	全ねじ Full Thread	CB 10-10	23				
		12					
		15					
		20					
25							
30							
35							
40							
45							
50							
55							
60							
65							
70							
75							
80							
85							
90							
95							
100							
110							
120							
130							
140							
150							
160							
170							
180							
190							
200							
210							
220							
230							
240							
250							
260							
270							
280							
290							
300							
310							
320							
330							
340							
350							
360							
370							
380							
390							
400							
410							
420							
430							
440							
450							
460							
470							
480							
490							
500							
510							
520							
530							
540							
550							
560							
570							
580							
590							
600							
610							
620							
630							
640							
650							
660							
670							
680							
690							
700							
710							
720							
730							
740							
750							
760							
770							
780							
790							
800							
810							
820							
830							
840							
850							
860							
870							
880							
890							
900							
910							
920							
930							
940							
950							
960							
970							
980							
990							
1000							

**RoHS** **CBHS**

六角穴付ボルトを削っている為頭に刻印文字の一部が残っている場合があります。

材質 SCM435 **S** 表面処理 四三酸化鉄皮膜 (Fe3O4)  
 硬度 38~43HRC  
 ネジ部 JIS B0205の2級 (ボルト精度 JIS B1176 強度区分 12.9)

ℓ	型式	標準単価	スライド1	スライド2	スライド3	スライド4
ℓ	型式	標準単価	スライド1	スライド2	スライド3	スライド4
全ねじ Full Thread	CBHS 3-5					
	6					
	8					
	10					
	12	4		50本	500本	1500本以上
	14			499本	1499本	
	15					
	16					
	18					
	20			1本		
	22			49本		
	25					
	30					
	35					
	40			50本	200本	1000本以上
45			199本	999本		
50						
55						
60			1本			
65			29本			
全ねじ Full Thread	CBHS 5-8					
	10					
	12					
	15					
	20					
	25					
	30					
	35					
	40					
	45					
	50					
	55					
	60					
	65					
	70					
75						
80						
85						
90						
95						
100						
110						
120						
130						
140						
150						
160						
170						
180						
190						
200						
210						
220						
230						
240						
250						
260						
270						
280						
290						
300						