


下型ダイセット用ボールガイドブッシュ・スプリング




PD 適用ボス寸径		d	D _{H4}	ℓ	A	B	L ₁	N	R	d ₁	型式		L	
Type	PD													
20	+0.020	26	37	0 -0.007	4	10	6	4	1.35	2.5	21.4	LBBS	20	50
22	+0.015	28	40								23		22	50 60
25		31	45								26		25	60 80
28	+0.025	36	50		5	12	7	4.5	1.65	3	30		28	60 80
32	+0.020	40	55						1.9		33.2		32	80 100
38	+0.030	48	64								40		38	80 100
45	+0.025	55	74								46.8		45	100 120
50	+0.035	60	83	0 -0.010	6	15	10	5	2.2	3.5	51.3		50	100 120
60	+0.030	70	95					2.7	61		60		100 120	

Order
注文例

 Delivery
出荷日 **3** 日目出荷  ストーク T
ストーク A



② ブシュの取付穴加工についてはP.1104を参照ください



D	D1	d	P	型式		FL 指定5mm単位	FL(自由長)											
				Type	PD		25	30	35	40	45	50	55	60	65	70	75	80
25	23.2	0.9	SWPB	SWPB	20	25 ~ 40	3.7	4.0	4.4	4.8	—	—	—	—	—	—	—	—
27	25.0	1.0			22	25 ~ 50	4.1	4.5	4.9	5.3	5.7	6.2	—	—	—	—	—	—
30	27.8	1.1			25	25 ~ 60	4.3	4.7	5.2	5.6	5.9	6.4	6.8	7.3	—	—	—	—
35	32.6	1.2			28	25 ~ 60	4.4	4.8	5.2	5.6	6.0	6.4	6.8	7.2	—	—	—	—
39	36.0	1.5			32	35 ~ 70	—	—	6.4	7.0	7.5	8.0	8.5	9.5	9.4	10.0	—	—
47	43.4	1.8			38	35 ~ 70	—	—	7.0	7.6	8.0	8.6	9.0	9.5	10.0	10.6	—	—
54	50.0	2.0			45	45 ~ 80	—	—	—	—	8.6	9.0	9.6	10.0	10.6	11.0	11.6	12.0
59	54.4	2.3			50	45 ~ 80	—	—	—	—	9.9	10.4	11.0	11.5	12.2	12.6	13.3	13.8
69	63.8	2.6			60	45 ~ 80	—	—	—	—	11.2	11.7	12.5	13.0	13.8	14.3	15.1	15.6

BALL RETAINERS

BALL RETAINERS ボールリテナ



PD 適用ポスト径		外径 φ D	内径 φ D1	ボール径 φ d	ボール数			型式		L	ページ	
					MBSH MBJH	MBS MBJ	比率	Type	PD			
10	MBSH (アルミ製) MBJH (樹脂製)	13.7	10.3	2	80	—	—	MBSH (アルミ製) MBJH (樹脂製)	10	25	P.1082	
					104	—	—			30		
					120	—	—			35		
13					100	—	—		13	25		
					130	—	—			30		
16		19.7	16.3		150	—	—			35		
					143	—	—			40		
					165	—	—			45		
20			3	198	—	—	20		30			
				99	—	—			35			
20	MBS (アルミ製) MBSH (アルミ製) MBJ (樹脂製) MBJH (樹脂製)	25.5		20.5		110			—	—	40	P.1144
						132			—	—	45	
22						154			—	—	50	
						140			—	—	55	
25						168			—	—	60	
		30.5		25.5		196			—	—	65	
28						165	96	172%	MBS (アルミ製)	20	50	
						180	112	161%			55	
32						228	140	163%			60	
						224	125	179%			65	
38	MBJ (樹脂製) MBJH (樹脂製)	30.5	25.5	3	266	160	166%	MBJH (樹脂製)	22	50	P.1144	
					350	208	168%			60		
45					204	126	162%			65		
					252	154	164%			70		
50					238	144	165%			75		
		39.5	32.5		294	176	167%			80		
60					350	208	168%	MBJ (樹脂製)	28	60		
					210	128	164%			65		
					238	144	165%			70		
					280	176	159%			75		
38	MBJ (樹脂製) MBJH (樹脂製)	47.5	38.5	5	320	198	162%	MBJH (樹脂製)	32	60	P.1144	
					400	234	171%			65		
45					360	220	164%			70		
					450	260	173%			75		
50					400	242	165%			80		
		59.5	50.5		460	264	174%			90		
60					500	286	175%	MBJ (樹脂製)	38	100		
					400	242	165%			110		
					460	264	174%			120		
					500	286	175%			130		

