

SAFETY DATA SHEET(SDS)

Creat date 25 Jan.2013
Revision date 29 Oct.2018

1. Identification of the substance or mixture and of the manufacturer

GHS product identifier	FELT PEN B (REP-B)
Manufacturer name	EIVEST CO.,LTD.
Address	2-4-11 Ohiraki Fukushima-ku Osaka City Osaka Pref. JAPAN
Section concerned	Quality control division
Tel	06-6463-2226
FAX	06-6463-2269
e-mail	info@eivest.com
Product Information Usage	
Acrylic lacquer coating	
Recommended use	
For industrial use	

2. Hazard(s) identification

GHS Classification	
Flammable liquids:	Category 2
Acute Toxicity	
Oral:	Not classified
Dermal:	Not classified
Inhalation: Gases:	No classification
Inhalation: Vapours:	Category 4
Inhalation: Dusts, Mists:	Not classified
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Sensitization	
Respiratory	Not classified
Skin	Category 1
Germ cell mutagenicity	Category 2
Carcinogenicity	Category 2
Reproductive toxicity	Category 1
Specific target organ toxicity - Single exposure	Category 1
Specific target organ toxicity - Repeated exposure	Category 1
Aspiration hazard	Classification not possible
Hazardous to the aquatic environment	
Short-term(acute) aquatic hazard:	Category 2
Long-term(chronic) aquatic hazard:	Category 2
Hazardous to the ozone layer	Classification not possible

Label Elements



Danger

Hazard statement:

May cause an allergic skin reaction
Suspected of causing genetic defects
Highly flammable liquid and vapour
Harmful if inhaled
Causes serious eye irritation
Toxic to aquatic life
May damage fertility or the unborn child
Causes damage to organs (state below for available organ data)
Causes damage to organs through prolonged or repeated exposure (state below for available organ data)
Toxic to aquatic life with long lasting effects
Suspected of causing cancer
Causes skin irritation
Causes damage to liver
Causes damage to organs (hematopoietic system)
Causes damage to respiratory system
Causes damage to respiratory system
Causes damage to kidney
Causes damage to systemic toxicity
Causes damage to central nervous system
May cause respiratory irritation
May cause drowsiness or dizziness
Causes damage to hematopoietic system through prolonged or repeated exposure
Causes damage to respiratory system through prolonged or repeated exposure
Causes damage to respiratory system through prolonged or repeated exposure
Causes damage to bone through prolonged or repeated exposure
Causes damage to nervous system through prolonged or repeated exposure
Causes damage to kidney through prolonged or repeated exposure
Causes damage to central nervous system through prolonged or repeated exposure
Causes damage to organ of hearing through prolonged or repeated exposure
May causes damage to liver through prolonged or repeated exposure
May causes damage to blood vessel through prolonged or repeated exposure
May causes damage to spleen through prolonged or repeated exposure

Precaution:

«Prevention»

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. -No smoking.
Use explosion-proof electrical/ventilating/lighting/equipment.
Ground/bond container and receiving equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.

Wear protective gloves/protective clothing/eye protection/suitable respiratory equipment.

Do not breathe dust/fume/gas/mist/vapours/spray.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing should not be allowed out of the workspace.

Do not eat, drink or smoke when using this product.

Wash hands thoroughly after handling.

Do not mix with other foreign materials.

If this is not the intended use, avoid release to the environment.

«Response»

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician, if you feel unwell.

If exposed or concerned: Get medical advice/attention.

IF ON SKIN(or Hair) : Take off immediately all contaminated clothing. Rinse skin with water/shower. Call a POISON CENTER or doctor/physician, if you feel unwell.

If skin irritation occurs: Get medical advice/attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists, get medical advice/attention.

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. Rinse mouth.

Collect spillage.

In case of fire: Use carbon dioxide, dry chemical powder, foam to extinction.

Get medical advice/attention, if you feel unwell.

«Storage»

Store in a well-ventilated place. Keep cool. Store locked up.

Keep out of reach of children.

«Disposal»

Dispose of contents/container in accordance with local/regional/national/international regulation.

Other hazards which do not result in classification

Physical and Chemical hazards

Very inflammable liquid. Remaining gas may cause explosion.

3. Composition/information on ingredients

Distinction of chemical or mixture:

Mixture

Hazardous, harmful element:

Chemical Name	Composition	CAS No.	Japanese Industrial Safety and Health Law (Article 57-2 of the Law)	Japanese PRTR Law
Butyl acetate	20 ~ 30%	123-86-4	Labeling/MSDS require	—
Ethylbenzene	10 ~ 20%	100-41-4	Labeling/MSDS require	1-53
Xylene, mixed isomers, pure	10 ~ 20%	1330-20-7	Labeling/MSDS require	1-80
Acrylic resin	10 ~ 20%	Confidential	—	—

Toluene	5 ~ 10%	108-88-3	Labeling/MSDS require	1-300
Ethyl acetate	5 ~ 10%	141-78-6	Labeling/MSDS require	—
Dibutan-1-yl phthalate	1 ~ 5%	84-74-2	Labeling/MSDS require	1-354
Cellulose, nitrate	1 ~ 5%	9004-70-0	Labeling/MSDS require	—
2-Propyl, 1-methoxy-, acetate	1 ~ 5%	108-65-6	—	—
Cyclohexanone	1 ~ 5%	108-94-1	Labeling/MSDS require	—
Polycarbonate	0.1 ~ 1%	25971-63-5	—	—
Diiron(III) trioxide	0.1 ~ 1%	1309-37-1	Labeling/MSDS require	—
Carbon black	0.1 ~ 1%	1333-86-4	Labeling/MSDS require	—
1-Butanol	0.1 ~ 1%	71-36-3	Labeling/MSDS require	—
Ethyl 3-ethoxypropanoate	0.1 ~ 1%	763-69-9	—	—
2-Propanol	0.1 ~ 1%	67-63-0	Labeling/MSDS require	—
Organic pigment	0.1 ~ 1%	Confidential	—	—
2-Butoxyethanol	0.1 ~ 1%	111-76-2	Labeling/MSDS require	—
Titanium dioxide	0.1 ~ 1%	13463-67-7	Labeling/MSDS require	—

4.First-aid measures

IF INHALED:

Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Call a POISON CENTER or doctor/physician if you feel unwell.

Remove the victim from the contamination immediately to fresh air and keep the victim warm and quiet.

In case breathing has stopped, loosen the clothing, secure respiratory tract, and conduct artificial breathing

Prevent from swallowing the vomiting.

Receive the treatment of a doctor immediately.

IF ON SKIN (or hair):

Wipe off contacted materials quickly with clothes.

Wash with plenty of soap and water.(Do not use solvent or thinner.)

If skin irritation occurs: Get medical advice/attention.

IF IN EYES:

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER or doctor/physician.

IF SWALLOWED:

Immediately call a POISON CENTER or doctor/physician.

Prevent from swallowing the vomiting.

Rinse mouth. Do NOT induce vomiting.

5.Fire-fighting measures

Suitable extinguishing media:

Carbon dioxide, Foam ,Dry chemicals

Unsuitable extinguishing media:

Water in a jet.

Specific hazards arising from the chemical:

Not available

Specific fire-fighting measures:

Don't use water.

Wear proper protective equipment(fire/flammable resistant/retardant clothing etc.).

Eliminate all ignition sources if safe to do so.

Use appropriate extinguishing media.

Cool container with water spray.

Fire-fighting shall be conducted from the windward of the fire as much as possible.

Special protective actions for fire-fighters:

Not available

6.Accidental release measures

Personal precautions,protective equipment and emergency procedures:

Wear proper protective equipment(Gloves/Protective mask/Protection clothes/Goggle etc.).

Evacuate non-essential personnel to safe area.

Extinguish naked flames and remove ignition sources.

Prepare proper fire-extinguisher for the fire.

Environmental precautions:

Pay attention so that the product that leaked is not discharged to the river or sewage, and have adverse effect on the environment.

Methods and materials for containment and cleaning up:

Collect leaking liquid in sealable containers.And remove to safe place.

Dispose of collected leakage in accordance with local/regional/ national/international regulations.

Take up the spill by equipment made of plastics to avoid sparks.

Absorb with sand or other non-combustible material.

Absorb remaining liquid in sand or inert absorbent and remove to safe place.

Prevention of secondary disaster:

Not available

7.Handling and storage

Precautions for safe handling

Handle in a place with good ventilation.

Keep container tightly closed.

Prohibit the use of high temperature objects, sparks, and fire in the vicinity of the product.

Equipment should be grounded and bonded. Use explosion proof electrical equipment.

Use only non-sparking tools.

Use antistatic working wear and shoes in operation.

Keep used-clothes, paint sludge and sprayed dust in water for waste disposal.

Use adequate exhaust ventilation in closed area and wear proper protective equipment during using this materials.

Wear protective gloves/protective clothing/eye protection/face protection.

Wash hands/face thoroughly after handling.

Conditions for safe storage, including any incompatibilities

Protect from sunlight.

Store in a well-ventilated place.

Keep away from fire and heat.

8.Exposure controls/personal protection

Equipment requirement:

Use non-spark closed type equipment.

Prevent remaining vapors with adequate ventilation.

Equipment should be grounded and bonded in case of transport, suction and stirring liquids.

Don't use equipment having high temperature and source of fire around handling this materials.

In poor ventilated area, use automatic spraying equipment and adequate ventilator to avoid direct workers' exposure to solvent vapors.

In the closed area of tank, use ventilator effective to closed and bottom area.

Control parameters:

	Administrative levels	Threshold limit value
Butyl acetate	150ppm	100ppm JSOH 150ppm ACGIH(TWA) 200ppm ACGIH(STEL)
Ethylbenzene	20ppm	50ppm JSOH 20ppm ACGIH(TWA)
Xylene,mixed isomers, pure	50ppm	50ppm JSOH 100ppm ACGIH(TWA) 150ppm ACGIH(STEL)
Toluene	20ppm	50ppm JSOH 20ppm ACGIH(TWA)
Ethyl acetate	200ppm	200ppm JSOH 400ppm ACGIH(TWA)
Dibutan-1-yl phthalate	Not applicable	5mg/m3 JSOH 5mg/m3 ACGIH(TWA)
Cyclohexanone	20ppm	25ppm JSOH 20ppm ACGIH(TWA) 50ppm ACGIH(STEL)
Diiron(III) trioxide	Not applicable	5mg/m3(Fe) ACGIH(TWA) 1 (Respirable dust)mg/m3 JSOH 4 (Total dust)mg/m3 JSOH
Carbon black	Not applicable	3.5mg/m3 ACGIH(TWA) 1 (Respirable dust)mg/m3 JSOH 4 (Total dust)mg/m3 JSOH
1-Butanol	25ppm	50ppm JSOH 20ppm ACGIH(TWA)
2-Propanol	200ppm	400ppm JSOH 200ppm ACGIH(TWA) 400ppm ACGIH(STEL)
2-Butoxyethanol	25ppm	20ppm ACGIH(TWA)
Titanium dioxide	Not applicable	10mg/m3 ACGIH(TWA)

Personal Protective Equipment(PPE)

Respiratory protection:

Use a respiratory protection mask for organic solvent gasses.

Use airline respirator at the closed place.

When spraying, wear an appropriate protective mask.

Hands protection:

Wear proper protective gloves(solvent / chemical resistance).

Eye/face protection:

Wear protective glasses.

Skin protection:

Wear protective gloves/protective clothing.

Workers should be wear electro conductive shoes during electrostatic spraying operation.

9.Physical and chemical properties

Appearance (physical state):	Liquid
Appearance (color):	Specific color
Odor threshold:	Solvent odour
pH:	No data
Boiling point:	77°C
Boiling range:	77~141°C
Flash point:	4°C
Lower flammability or explosive limits:	1Vol%
Upper flammability or explosive limits:	11.4Vol%
Vapor pressure:	12452Pa
Density:	0.94g/cm3
Auto-ignition temperature:	425°C

10.Stability and reactivity

Reactivity/Chemical stability:

Product is considered stable under normal storage and handling conditions.

Possibility of hazardous reactions:

Not determined.

Conditions to avoid:

Store at temperatures not exceeding 40 °C. Keep cool.

Incompatible materials:

Oxidizing substances

Hazardous decomposition products:

In combustion: Generate dangerous gasses such as CO, low-molecular weight monomers,NOx gasses.

11.Toxicological information

	Acute Toxicity Oral	Acute Toxicity Dermal	Acute Toxicity Inhalation: Gases	Acute Toxicity Inhalation: Vapours	Acute Toxicity Inhalation: Dusts, Mists
Butyl acetate	Not classified	Not classified	No classification	Classification not possible	Classification not possible
Ethylbenzene	Not classified	Not classified	No classification	Category 4	Classification not possible
Xylene,mixed isomers, pure	Not classified	Category 4	No classification	Category 4	Classification not possible

	Acute Toxicity Oral	Acute Toxicity Dermal	Acute Toxicity Inhalation: Gases	Acute Toxicity Inhalation: Vapours	Acute Toxicity Inhalation: Dusts, Mists
Acrylic resin	Not classified	Not classified	No classification	No classification	Classification not possible
Toluene	Not classified	Not classified	No classification	Category 4	Classification not possible
Ethyl acetate	Not classified	Not classified	No classification	Category 4	Classification not possible
Dibutan-1-yl phthalate	Not classified	Not classified	No classification	Classification not possible	Not classified
Cellulose, nitrate	Not classified	Classification not possible	No classification	Classification not possible	Classification not possible
2-Propyl, 1-methoxy-, acetate	Not classified	Not classified	No classification	Classification not possible	Classification not possible
Cyclohexanone	Category 4	Category 3	No classification	Category 3	Not classified
Polycarbonate	Not classified	Not classified	No classification	Classification not possible	Classification not possible
Diiron(III) trioxide	Classification not possible	Classification not possible	No classification	Classification not possible	Classification not possible
Carbon black	Not classified	Classification not possible	No classification	No classification	Classification not possible
1-Butanol	Not classified	Not classified	No classification	Classification not possible	Not classified
Ethyl 3-ethoxypropanoate	Not classified	Not classified	No classification	Classification not possible	Classification not possible
2-Propanol	Not classified	Not classified	No classification	Not classified	Classification not possible
Organic pigment	Not classified	Classification not possible	No classification	Classification not possible	Classification not possible
2-Butoxyethanol	Category 4	Category 3	No classification	Category 2	Classification not possible
Titanium dioxide	Not classified	Not classified	No classification	Classification not possible	Not classified

	Skin corrosion/irritation	Serious eye damage/eye irritation	Respiratory sensitization	Skin sensitization	Germ cell mutagenicity
Butyl acetate	Not classified	Category 2B	Classification not possible	Classification not possible	Classification not possible
Ethylbenzene	Not classified	Category 2B	Classification not possible	Classification not possible	Classification not possible
Xylene, mixed isomers, pure	Category 2	Category 2	Classification not possible	Classification not possible	Not classified
Acrylic resin	Classification not possible	Classification not possible	Classification not possible	Classification not possible	Classification not possible
Toluene	Category 2	Category 2B	Classification not possible	Not classified	Not classified
Ethyl acetate	Not classified	Category 2B	Classification not possible	Not classified	Not classified
Dibutan-1-yl phthalate	Not classified	Not classified	Classification not possible	Category 1	Classification not possible
Cellulose, nitrate	Classification not possible	Classification not possible	Classification not possible	Classification not possible	Classification not possible
2-Propyl, 1-methoxy-, acetate	Not classified	Category 2B	Classification not possible	Not classified	Classification not possible
Cyclohexanone	Category 2	Category 2A	Classification not possible	Category 1	Category 2
Polycarbonate	Classification not possible	Classification not possible	Classification not possible	Classification not possible	Classification not possible

	Skin corrosion/irritation	Serious eye damage/eye irritation	Respiratory sensitization	Skin sensitization	Germ cell mutagenicity
Diiron(III) trioxide	Category 2	Classification not possible	Classification not possible	Classification not possible	Classification not possible
Carbon black	Not classified	Not classified	Classification not possible	Classification not possible	Classification not possible
1-Butanol	Category 2	Category 2A	Classification not possible	Classification not possible	Classification not possible
Ethyl 3-ethoxypropanoate	Not classified	Category 2B	Classification not possible	Classification not possible	Classification not possible
2-Propanol	Not classified	Category 2	Classification not possible	Classification not possible	Classification not possible
Organic pigment	Not classified	Not classified	Not classified	Not classified	Classification not possible
2-Butoxyethanol	Category 2	Category 2A	Classification not possible	Not classified	Classification not possible
Titanium dioxide	Not classified	Category 2B	Classification not possible	Classification not possible	Not classified
	Carcinogenicity	Reproductive toxicity	Specific target organ toxicity - Single exposure	Specific target organ toxicity - Repeated exposure	Aspiration hazard
Butyl acetate	Classification not possible	Classification not possible	Category 3	Classification not possible	Classification not possible
Ethylbenzene	IARC(2B)	Category 1B	Category 3	Category 2	Category 1
Xylene,mixed isomers, pure	IARC(3)	Category 1B	Category 1	Category 1	Category 1
Acrylic resin	Classification not possible	Classification not possible	Classification not possible	Classification not possible	Classification not possible
Toluene	IARC(3)	Category 1A	Category 1	Category 1	Category 1
Ethyl acetate	Classification not possible	Classification not possible	Category 3	Classification not possible	Classification not possible
Dibutan-1-yl phthalate	Classification not possible	Category 1B	Category 3	Category 1	Classification not possible
Cellulose, nitrate	Classification not possible	Classification not possible	Category 3	Classification not possible	Classification not possible
2-Propyl, 1- methoxy-, acetate	Classification not possible	Not classified	Category 3	Classification not possible	Classification not possible
Cyclohexanone	IARC(3)	Category 2	Category 1	Category 1	Classification not possible
Polycarbonate	Classification not possible	Classification not possible	Classification not possible	Classification not possible	Classification not possible
Diiron(III) trioxide	IARC(3)	Classification not possible	Category 3	Category 1	Classification not possible
Carbon black	IARC(2B)	Classification not possible	Classification not possible	Category 1	Classification not possible
1-Butanol	Classification not possible	Classification not possible	Category 3	Category 1	Classification not possible
Ethyl 3-ethoxypropanoate	Classification not possible	Classification not possible	Category 3	Classification not possible	Classification not possible
2-Propanol	IARC(3)	Category 2	Category 1	Category 1	Classification not possible
Organic pigment	Classification not possible	Classification not possible	Classification not possible	Classification not possible	Classification not possible
2-Butoxyethanol	IARC(3)	Category 2	Category 1	Category 1	No classification
Titanium dioxide	Classification not possible	Classification not possible	Classification not possible	Classification not possible	Classification not possible

12. Ecological information

Toxicity:

No data

Persistence and degradability:

No data

Bioaccumulative potential:

No data

Mobility in soil:

No data

Other adverse effects:

The product should not be allowed to enter drains or water courses.

Hazardous to the aquatic environment/Hazardous to the ozone layer:

	Short-term(acute) aquatic hazard	Long-term(chronic) aquatic hazard	Hazardous to the ozone layer
Butyl acetate	Category 3	Not classified	Classification not possible
Ethylbenzene	Category 1	Category 2	Classification not possible
Xylene,mixed isomers, pure	Category 2	Category 2	Classification not possible
Acrylic resin	Classification not possible	Classification not possible	Classification not possible
Toluene	Category 2	Category 3	Classification not possible
Ethyl acetate	Not classified	Not classified	Classification not possible
Dibutan-1-yl phthalate	Category 1	Category 2	Classification not possible
Cellulose, nitrate	Not classified	Not classified	Classification not possible
2-Propyl, 1-methoxy-, acetate	Not classified	Not classified	Classification not possible
Cyclohexanone	Not classified	Not classified	Classification not possible
Polycarbonate	Classification not possible	Classification not possible	Classification not possible
Diiron(III) trioxide	Classification not possible	Classification not possible	Classification not possible
Carbon black	Not classified	Classification not possible	Classification not possible
1-Butanol	Not classified	Not classified	Classification not possible
Ethyl 3-ethoxypropanoate	Not classified	Not classified	Classification not possible
2-Propanol	Not classified	Not classified	Classification not possible
Organic pigment	Classification not possible	Classification not possible	Classification not possible
2-Butoxyethanol	Not classified	Not classified	Classification not possible
Titanium dioxide	Classification not possible	Classification not possible	Classification not possible

13. Disposal considerations

Description of waste residues and information on their safe handling and methods of disposal

Dispose of contents/container in accordance with local/regional/ national/international regulations.

Don't wash away the used for cleaning of vessels and equipment into shower or water way.

The wastes producing from process of water refining and of incineration should be disposed of in accordance with governmental laws and environmental control regulations or asked to dispose with licensed special company.

Waste paints and opened containers should be asked to dispose with licensed industrial waste treatment company.

Disposal of any contaminated packaging

Remove the contents completely before disposing of them.

Dispose of contents/container in accordance with local/regional/ national/international regulations.

14. Transport information

Special precautions for user:

See Section 7.

Verify that there is no damage or leakage of the containers, and load them so that there are no shock, tumbling, dropping, or container damages, and conduct load collapse prevention securely.

Regulation by Japanese law:

Transport this product in compliance with the Firefighting Law, Law of Industrial Safety & Hygiene and Poisonous & Deleterious Material Control Law, if any.

According to providing in IMDG Code/Japanese Ship Safety Act.

According to providing in ICAO TI/Japanese Civil Aeronautics Act.

UN Number:

1263

UN Proper shipping name:

PAINT or PAINT RELATED MATERIAL

Transport Hazard class(es):

128 FLAMMABLE LIQUIDS (Non-Polar / Water-Immiscible)

UN classification:

Class 3 : Flammable liquids

Packing group, if applicable:

II

Marine pollutant:

It doesn't correspond to regulations.

Special precautions which a user needs to be aware of or needs to comply with in connection with transport or conveyance either within or outside their premises:

It doesn't correspond to regulations.

15. Regulatory information

<Products>

Japanese Law on Industrial Safety and Hygiene Enforcement Ordinance Attached Table 1-4 Inflammable substance

Japanese Law on Industrial Safety and Hygiene Enforcement Ordinance Attached Table 6-2 Article 1, Item 1, Sub-item 4 of Organic Solvent Poisoning Prevention Regulation Class 2 organic solvent

Japanese Ordinance on the Prevention of the Hazards due to Specified Chemical Substances Article 2 Class 2 substance

Japanese Fire Services Act Article 2 Hazardous Substance Attached Table Class 4
Inflammable liquid. (No. 1 Petroleum / Non-water-soluble liquid)

Japanese Port and Harbor Law Enforcement Regulation Article 12 Hazardous Material
Notification Inflammable liquid class

Japanese Air Navigation Law Enforcement Ordinance Article 194 Hazardous Material
Notification Attached Table 1 Inflammable Liquid

We are not able to check up the regulatory information in regard to the substances in your
country or region,therefor, we request this matter would be filled by your responsibility.

<Butyl acetate>

Japanese Law on Industrial Safety and Hygiene Enforcement Ordinance Attached Table 6-
2 Article 1, Item 1, Sub-item 4 of Organic Solvent Poisoning Prevention Regulation Class
2 organic solvent

<Ethylbenzene>

Japanese Ordinance on the Prevention of the Hazards due to Specified Chemical
Substances Article 2 Class 2 substance

Japanese Chemical Substances Control Law, Article 2, section 5, Chemical substances
requiring prior assessment

<Xylene,mixed isomers, pure>

Japanese Law on Industrial Safety and Hygiene Enforcement Ordinance Attached Table 6-
2 Article 1, Item 1, Sub-item 4 of Organic Solvent Poisoning Prevention Regulation Class
2 organic solvent

Japanese Foul Odor Prevention Law Enforcement Ordinance Article 1. Specified foul odor
substance.

Japanese Chemical Substances Control Law, Article 2, section 5, Chemical substances
requiring prior assessment

<Toluene>

Japanese Law on Industrial Safety and Hygiene Enforcement Ordinance Attached Table 6-
2 Article 1, Item 1, Sub-item 4 of Organic Solvent Poisoning Prevention Regulation Class
2 organic solvent

Japanese Foul Odor Prevention Law Enforcement Ordinance Article 1. Specified foul odor
substance.

Japanese Chemical Substances Control Law, Article 2, section 5, Chemical substances
requiring prior assessment

<Ethyl acetate>

Japanese Law on Industrial Safety and Hygiene Enforcement Ordinance Attached Table 6-
2 Article 1, Item 1, Sub-item 4 of Organic Solvent Poisoning Prevention Regulation Class
2 organic solvent

Japanese Foul Odor Prevention Law Enforcement Ordinance Article 1. Specified foul odor
substance.

<Cyclohexanone>

Japanese Law on Industrial Safety and Hygiene Enforcement Ordinance Attached Table 6-
2 Article 1, Item 1, Sub-item 4 of Organic Solvent Poisoning Prevention Regulation Class
2 organic solvent

Japanese Chemical Substances Control Law, Article 2, section 5, Chemical substances
requiring prior assessment

<1-Butanol>

Japanese Law on Industrial Safety and Hygiene Enforcement Ordinance Attached Table 6-
2 Article 1, Item 1, Sub-item 4 of Organic Solvent Poisoning Prevention Regulation Class
2 organic solvent

Japanese Chemical Substances Control Law, Article 2, section 5, Chemical substances
requiring prior assessment

<2-Propanol>

Japanese Law on Industrial Safety and Hygiene Enforcement Ordinance Attached Table 6-

2 Article 1, Item 1, Sub-item 4 of Organic Solvent Poisoning Prevention Regulation Class 2 organic solvent

Japanese Chemical Substances Control Law, Article 2, section 5, Chemical substances requiring prior assessment

<2-Butoxyethanol>

Japanese Law on Industrial Safety and Hygiene Enforcement Ordinance Attached Table 6-2 Article 1, Item 1, Sub-item 4 of Organic Solvent Poisoning Prevention Regulation Class 2 organic solvent

Japanese Chemical Substances Control Law, Article 2, section 5, Chemical substances requiring prior assessment

16.Other information

Reference

Chemical Risk Information Platform (CHRIP) (National Institute of Technology and Evaluation(NITE))

Globally Harmonized System of classification and Labeling of chemicals,(3rd ed.,2009),UN SDS & Labeling guide book(rev. 1st ed., March 2007),JPMA

Chemical data base for paint(5th ed.,Mar. 2009)(1st ed.,May 2007),JPMA

International Chemical Safety Cards(ICSC)

Supplier's SDS

This information is contained in this safety data sheet represents the best information currently available to us. However, no warranty is made with respect to its completeness and we assume no liability resulting from its use. It are advised to make their own tests to determinate the safety and suitability of each such product or combination for their own purposes.
